

15.6 15.1 Andorid/Windows POS

(M/N POS-H156/H151)

OCOM H pos

IO



Intel Celeron Intel Core I3 I5

Rockchip RK3568

EMMC 8GB/16GB/32GB

Msata SSD 64GB SSD 128GB 256GB

58mm 80mm

MSR VFD220

	POS-H156	POS-H151
	15.6 POS	15.1 POS

□□	□□□□□□□□	
□□	□□□□□□□□□□□□□□□□□□	
□□		
□□□	15.6□□□□□□□□	15.1□□□□□□□□
□□□	1366*768	1024*768
□□	250cd/□□□	
□□	□□□□150□□□□140	
□□□	□□□□GG□□□□	
□□	15.6/14/11.6□□□□□□□□□□□□□□□□ □1366*768□□	15.1□□□□□□□□□□□□□□□□□□ □1024*768
□□	2*20 VFD□□□□□□□□□□	
□□		
WindowsJ4125	□□	Intel Celeron J4125, 2.0GHz □ intel core I3 / I5 4th CPU □□□□
	□□□□	1*SO-DIMM DDR4□□□□□2400 mHZ□4GB/8GB□□
	□□□□	Msata SSD 64GB □□□□□□□ 256GB
	□□	□□Real Tek ALC662□□□□
	□□□	10/100Mbs□Realtek RTL8111F □□□□ □□Mini PCI-E□□□□□□□□□WIFI□□
	□□□□	Windows10/11
□□RK3568	□□	Rockchip□□RK3568□□□2.0G□RK3399□□
	□□□□	□□DDR4 2GB□4GB□□□□
	□□□□	□□16GB EMMC□□□32GB
	□□□	RJ45□□□□10/100Mbs□□□
	WIFI&□ □□□	□□Wi-Fi 802.11b/g/n□□□BT3.0/BT4.0
	□□□□	□□11
□□□		
Windows/□ □(J4125&RK3568)	□□□□*1	
	12V DC □□□□*1	
	□□□□RJ-45*1	
	USB*6	
	□□□□□*1□□□□□*1	
Windows(J4125)	□□(RS232) *1 □ HDMI*1 □□□□	
	VGA(15□D-sub)*1	
	RJ11 □□□□□□ *1 □□	

	COM(RS232) *1
□□(RK3568)	□□RJ11□□□□*1□□RJ11□□□□□□□□□□□□*1□□□□
	TF□□*1
□□	
80□□□□□□□□	□□□□□□
	100mm/s □□□□
	79.5-/ 0.5mm□□□□□□□□72mm
	□□□□□□□□□□□□□□50km
	LPT□□
58□□□□□□□□	□□□□□□
	85mm/s □□□□
	57.5-/ 0.5mm□□□□□□□□48mm
	□□□□□□50km
	LPT□□
MSR	□□□□MSR
□□□□□□	□□□□□□□□□□□□□□□□
□□□	□□□□&□□□□□□□□
□□□	□□4□□/5□□□□□□□□□□
□□	
□□	□□□5.6Kg□□□□□7.7Kg□15.6□15.6□□/□□□□□□□□
□□□□□□□□	340*450*480□□
2□1□□	700*460*500mm / □□□17kg
□□	
□□□□	0□40□□□□
□□□□	-10□60□□□□
□□□□	10%~80%
□□□□	10%~90%
□□	
□□□□□□	110-240V/50-60HZ □□□□□□□□DC12/5A □□□□□□□□ W/o □□□□ W/58mm □ □□ DC12V/7A □□□□□□□□□□ W/80mm □□□□
□□□	□□□□□□□□□□/□□□/□□□□□□□□□□
□□	□□□□□□□□□□□□□□□□□□
□□	



FCC A /CE /LVD/CCC



All In One Touch Screen POS System



Product Display

15.6 or 15.1 inch zero-bezel touch screen for optional

Multi-point projected capacitive touch panel

Built-in 58mm or 80mm thermal printer for optional

Barcode scanner inbuilt for option

Ture flat and water-proof scratch-resistant surface display



Accessories



Thermal Printer



Barcode Scanner



Cash Drawer



Card Reader



Product
Accessories

SUPPORT SYSTEMS



WINDOWS



ANDROID



LINUX

Product Interface


Windows interfaces J1900/i3/i5




DC




COM(RS232) *1 or HDMI*1 for option



VGA



LAN



RJ11(optional)



USB *6




MIC-IN Audio-OUT


Android interfaces RK3288




DC



COM



LAN



RJ11(optional)*2



USB *6



TF Card



MIC-IN Audio-OUT

Screen Size



↙↘ 15.6 inch

or



↙↘ 15.6 inch

+

15.6 inch

14.0 inch

11.6 inch

2*20 VFD



↙↘ 15.1 inch

or



↙↘ 15.1 inch

+

15.1 inch

2*20 VFD

Product Color



Product Details







□□□□

[POS-H15 58mm□□□□](#)

[POS-H15 80mm□□□□](#)

[POS-H15□□□Android SDK](#)

