

21.5 Windows/ POS

M / N POS - K003

;  
;  
;  
;  
;  
;  
;  
;  
;

	POS-K003-W	POS-K003-A
	21.5 Windows/ POS	
	21.5	21.5
	1920 * 1080	1920 * 1080
	250cd / m2	
	178 178	
	10G+G	
	Intel Bay Trail J1900 2.0GHz / Intel core I3 / I5 CPU	ARM Cortex-A17 -RK 3288 1.8GHz CPU
	1 * SO-DIMM DDRIII 1333 */1600 4GB	2GB DDRIII
	Msata SSD 64GB	16GB EMMC
	Real Tek ALC662	Real Tek ALC5640
LAN	10/100Mbs, Realtek RTL8111F Lan	10M/100M, RTL8201F
WIFI	802.11 a / b / g	802.11 a / b / g
	8 / 10	
	Windows 7/8/10, Embedded, WEPOS, Linux	Android 7.1
I/O (J1900/RK3288)	* 1 100V-240V 50Hz / 60Hz AC * 1 USB * 2 LAN RJ-45 * 1	
	617nm LED	
	5V DC	
1D	UPC EAN Code 128 Code 39 Code 93 Code 11 Interleaved 2 of 5 Matrix 2 of 5 Codabar MSI Plessey GS1 DataBar Maxicode Micro QR Aztec.....	
2D	PDF417 Micro PDF417 Maxicode Micro QR Aztec.....	
	4 mil code 39	

□□□□□□	□□:±60°@ 0°□□□0°□□ □□:360°±@ 0°Pitchand0°□□ □□:±65°@ 0°□□□0°□□
□□□□	□□□□
□□	USB
□□□□	
80mm□□□□□□	□□□□ 150mm / s 79.5 - / + 0.5mm□□□□□72mm□□□□□ □□□□ Power DC 24V □□□ 203dpi
□□	
□□□□	0 □40 □□□
□□□□	- 10 □60 □□□
□□□□	10□□80□ □□□□
□□□□	10□□90□ □□□□
□□	
□□□□	□□□□□□□□□□/□□□□□□□□□□
□□	□□□□□□□□□□(□□)
□□	
□□	FCC A□ / CE Mark / LVD / CCC



POS-K003





POS-K003





POS-K003







POS-K003



