

□□□Pos□□□USB□□58□□□□□□□□□□□□

□□□□OCPP -C582□

□□□

120 mm / s□□□□□□□

□□□□□□□□□□

□□□□□□□□□□□□□□

□□USB□□

LAN□□□□USB + BT□□USB + WIFI□□□□□

□□□□□□□□

□□nv□□□□□

□□□□□□

□□ESC / POS□□

□□□□□□□50KM

□□□□□□60□□

□□□

□□□□	□□□□
□□□□	384□/□□203DPI□
□□□□	384□/□□ANK□□□□□□A□12 * 24□□1.5□W□* 3.0□H□mm □□/□□□24 * 24□□3.0□W□* 3.0□H□mm
□□□□	JAN13□EAN13□JAN8□EAN8□CODE39 / CODE128 / CODABAR / ITF
□□□□	□EPSON ESC / POS□□
□□□□	120□□/□
□□	57.5±0.5□□
□□□□	60□□
□□□□	0.06-0.08□□
MCBF□□□□□	50□□
□□□□	60□□
NV□□	64kb□
□□□□	32kb□
□□	169.9 * 120 * 119.9□□

重量	1.2kg
尺寸	100mm
接口	USB + LAN + USB + wifi
兼容性	USB + LAN + USB + wifi 兼容性 = 180
操作系统	ESPON Win 9X Win 2000 Win 2003 Win XP Win Vista Win 7 win8 win10
电源输入	AC110V / 220V 50-60Hz
电源输出	DC12V / 2.6A
工作电压	DC12V / 1A
工作温度	0-45°C 湿度 10-80%
存储温度	-10-60°C 湿度 10-90%
认证	CE / FCC / CCC / RoHS



OCPP-C582





OCPP-C582







OCPP-C582





OCPP-C582





OCPP-C582

