

□□□□□□□□□□□□

□M / N□OCBP -201□

□□□

USB□USB +□□□□□□

□□□□□□□□

□□□□□□□□

□□□□□□□□□□□□

□□TSPL□ESC / POS□□

□□□□□□□□□□□□□□

□□□□	□□□□
□□□	203DPI
□□	TSPL□ESC / POS
□□□□	□□□□□□□□□□□□ □□□□HEX□1F 1B 1F 02 20 n 0D 0A□n = 31 / 30.default n = 30□
□□□□	20-60mm□
□□□□□□	MAX□101□□/□; MIN□50.8□□/ s□
□□	DRAM□256kb FLASH□576kb
□□□□□□	□□□□□
□□□□□□	□□□□□
□□	USB□USB +□□
□□□□□□□□	□□□□□□□□
□□	CODE128□EAN128□ITF□CODE39□CODE93□EAN13□EAN13 + 2□ EAN13 + 5□EAN8□EAN8 + 2□EAN8 + 5□CODABAR□POS TNET□UPC-A□UPCA + 2□UPCA + 5□UPC-E □UPCE + 2□UPC-E + 5□C POS T□MSI□MSIC□PLESSEY□ITF14□EAN14 Qrcode□DM□ □□PDF417
□□□□□□□□□□	□0°□90°270°□360°□□□□□□□□1□10□; 0°□90°□270°□360°□□
□□	□□PCX□BMP□□□□□□□□□□□□FLASH
□□□□□□	□□□□□□□□□□□□□□
□□□□□□	20□□□60□□□
□□□□□□	□□80□□
□□□□□□	□□25□□
□□□□□□	□□
□□□□□□	DC12V□3A
□□□□□□	5~45°C□□□□□□□20-80□□□□□□□□
□□	-40□55°C□≤93□RH□40°C□
□□	



