

# Android Terminal

M / N OCBS -D7000

## Product Description

Android 7.0  
2 GB RAM 16 GB ROM  
4.0" 480 \* 800 WVGA IPS  
1D / 2D  
RFID LF / HF / UHF / for optional  
& Functional keyboards  
4G / Wifi / GPS /  
5 MP LED  
3.7V 5200 mAh  
IP65 / 1.5 m

158mm x 75mm x 28mm ±2mm  
300mm  
4.0" TFT-LCD WVGA 480x800  
LED  
3TP 17mm x 4mm  
2PSAM 1SIM 1TF  
3.7V 5200mAh

Cortex A7 1.2 GHz  
Android 7.0  
2 GB RAM 16 GB ROM MicroSD 32 GB

-20°C 50°C  
-20°C 70°C  
5% 95% RH  
5 / 1.5  
IP65 IEC  
±15kV ±8kV ±8kV

HHW  
Java  
Android Studio Eclipse

□□□□

WWAN

WCDMA□850/1900 / 2100MHz□□GSM / GPRS / Edge 850/900/1800 / 1900MHz□

WLAN

IEEE 802.11 b / g / n

WPAN

□□Class v2.1 + EDR□□□v3.0 + HS□□□v4.0

□□□□□□

GPS□□□□A-GPS□□□□□5□

□□□□□□

□□□□□□□□□□

1D□□□□

□□□□□□ □□□□N431x

□□ □□□□□□□□□□

2D CMOS□□□□ □□□□N6603

□□□□

PDF417□MicroPDF417□Com pos  
ite□RSS□TLC-39□Datamatrix□QR□□Micro QR  
□□Aztec□MaxiCode□Pos tcodes□US Pos tNet□US Planet□  
UK Pos tal□Australian Pos t□Japan Pos t□Dutch Pos t□□  
□

□□□□□□

□□□□

500□□□□

□□

□□LED□□□□□□□□□□

**RFID**□□□□□□□□

RFID LF

□□ 125KHz / 134.2KHz□FDX-B / HDX□

□□ ISO 11784& 11785

R / W□□ 2□□□10□□

□□ 13.56MHz□

RFID HF

□□ ISO 14443A& 15693

R / W□□ 2□□□8□□

**PSAM**□□□□□□□□

□□

ISO 7816

□□□□

9600,19200,38400,43000,56000,57600,115200

□□

2□□□□□□□□

□□□□

□□

1x□□

1XLithium□□□□□□

1xDC□□□□

1xUSB□□□□

□□□□

□□□□□□

▶ Picture Show



# OCBS-D7000





OCBS-D7000





# OCBS-D7000





# OCBS-D7000





# OCBS-D7000





OCBS-D7000







# OCBS-D7000





## ▶ Company



## ▶ Certificates



## ▶ Payment



## ▶ Contact us



tePay CartaSi 4B Euro6000

5.

6.

Eruopean

159 2300 O2 500 ..... 50

OCOM

- 500 POS Auto-ID
- O2 Star .....
- 2300 159;
- 11 OEM / ODM
- POS
- 
- ISO FCC CE Soncap POA BIS
- 12 + 1
- “”
- 

OCOM Technologies Ltd. TUV POS Auto-ID

OCOM POS POS POS POS ISO CE FCC

OCOM “” OEM / ODM