

USB
OCBS-LA11

Specifications

Wavelength	650-670nm
Power	200mW
Beam Diameter	2.5~600mm @ 100µm UPC / EAN
Beam Quality	1
Surface Finish	PCS 0.9µm @ 0.10mm @ 4mil
Surface Reflectance	30% @ 650nm
Material	Aluminum
Dimensions	UPC / EAN, UPC / EAN, UCC / EAN, 128, 39, 39, ASCII, 39 trioptic, 128, 128, ASCII, codabar, 2 of 5, 2 of 5, 93, MSI, 11, ATA, RSS, 2 of 5 ...
Interfaces	PS2, RS232, USB
Voltage	DC + 5V +/- 5%
Current	100mA
Power Consumption	< 40mA
Connectivity	RS232
Viewing Angle	45° ~ 60°
Dimensions	L165mm X W63mm X H87mm
Weight	129g
Material	Aluminum
Material	Aluminum
Operating Temperature	0°C ~ 40°C
Storage Temperature	-40°C ~ 60°C
Humidity	5% ~ 95%
Electrostatic Discharge (ESD)	+/- 15KV, +/- 8KV
Shock	1.5g
EMI / RFI	FCC A, CE
Regulatory	CDRH 2

Notes



OCBS-LA11





OCBS-LA11





OCBS-LA11





OCBS-LA11





OCBS-LA11



□□□□

□□□□□□□□ information □□ □□□□

□□
□□□□