

Windows / Android 15.6 POS

POS -15T01-W / A



□□□

□□□□□□□□;

15.6□□1366 * 768□□□□□□□□;

360□□□□□□□□;

□□Windows□Android□□;

□□□□□□□□;

□□□□□15.6□□□11.6□□□□□□□□;

MSR□□□□□□□□;

□□□□□□□□□□□□□□□□□□□□

□□□

□□□□□□□□□□□□□□□□□□□□□□□□;

□□□□□□□□□□□□□□□□□□□□□□□□;

□□□□□□□□□□□□□□□□□□□□□□□□;

□□□□□□□□□□□□□□□□□□□□□□□□

□□□□

□□	POS -15T01-W / A□□□□Windows□□□□Android□A□
□□①	□□□□Windows□□□□□1.99 GHz J1900N
□□②	□□□□Android□□□□□1.8GHz RK3288
Windows□□□□	Windows 7 □□□□
Android□□□□	Android 6.0
Windows RAM	2GB□□ 4GB 8GB□□
Android□□	2GB
Windows□□	32GB SSD□□□□64GB□128GB□□
Android□□	8GB eMMC□□□□32GB TF□□□
□□□□	15.6□□□□□
□□□□	15.6□□□□11.6□□
□□□□	VFD□LCD
□□□	1366 * 768
□□□	□□□□□□□□
□□	□□350cd /□ ²
□□	□□□□150;□□□140
J1900 I / O□□	VGA * 1□USB * 5□RS232 * 1□DC□□* 1 RJ45□□□□□□□□* 1□□□□□□* 1
RK3288 I / O□□	USB * 5□RS232 * 2□DC□□* 1□RJ11□□□□□□□□□□* 1 RJ45□□□□□□□□* 1□□□□□□* 1□MIC * 1
□□□□	0□40□□□□
□□□□	-20□60□□□□
□□□□□□	110-240V / 50-60HZ□□□□□□□□□□DC12 / 5A□□



POS-15T01





POS-15T01





POS-15T01





POS-15T01





POS-15T01





POS-15T01





POS-15T01





POS-15T01



