

usb 2d

OCBS -LA09

000

0000	
0000	650nm
0000	200
00000	32
0000	2.5~600mm 100 UPC / EAN
0000	50mm @ 60mm 220mm @ 200mm
000000	
0000	
0000	3mil / 5mil
00000000	30
00000	UPC / EAN UPC / EAN UCC / EAN 128 Code 39 Code 39 ASCII Trioptic Code 39 Code 128 Code 128 Full ASCII Codabar Interleaved 2 of 5 Discrete 2 of 5 Code 93 MSI Code 11 RSS 2 of 5 MSI / Plessey UK / Plessey UCC / EAN 128 GS1 DataBar RSS
0000	±65°; ±60°; ±42°
0000	
000000	PS2 RS232 USB
000	5V DC ±5
000	85 mA; 100
000	LED
00	ABS + PC
00	
00000	156 * 68 * 83 mm * * *
000	235
000	
0000	
00000	0°C 45°C
00000	-40°C 60°C
000	5-90
00000	+/- 15KV +/- 8KV
0000	0~100,000 LUX
00000	1.5
0000	EN60825-1 Class 1

00000



*Handheld Laser
Barcode Scanner*

OCPP-LA09



Product Picture





Features

Simple but not easy

200scan/sec high scan rate and long reading distance;





Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined with future-proofing





Competitive price for 32bit model



|| All-round show





Parameter

Performance Characteristics	
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	Auto Sense
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	30%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar

	Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code , GS1 DataBar (RSS) series
Scanning Angle	±65°(tilt); ±60°(pitch); ±42°(yaw)
Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	5V DC±5%
Current:	85 mA (Operating); 100 (Max)
Indicator	Beeper, LED
Material	ABS+PC
Stand	Optional
Dimensions:	156*68*83 mm (L*W*H)
Weight:	235g
Color:	Grey and black
User Environment	
Operating Temperature:	0℃~45℃
Storage Temperature:	-40℃~60℃
Humidity:	5%-90% (non-condensing)
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge
Ambient Illumination	0 ~ 100,000 LUX
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface
Laser classification	EN60825-1, class 1

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which

4. 注册与

注册与
t / twestern uion paypal
aliexpress http://www.aliexpress.com/store/403448 tracelog
= minisite_CI factorie

5. 注册

* 1 12000 1
2 3
4 CRM 5 6
7 * 24 4 12

6. 注册

http:// www pos solution.com.cn/cn/download.html SDK

7. 注册

http:// www pos solution.com.cn/video.html

8. 注册