

USB

OCBS -2018

Feautre

1MP

1280 * 800

4mil

1D 2D

4mil

4mil

4mil

4mil

USB	RS232	USB; RS232
OS	Linux, Android, Windows XP, 7, 8, 10, MAC	Linux, Android, Windows XP, 7, 8, 10, MAC
Interface	UART, SPI, I2C, CAN, RS485	UART; SPI; I2C; CAN; RS485
Sensor	CMOS	CMOS
Light	LED + LED	LED + LED
Processor	32 ARM MCU + DSP	32 ARM MCU + DSP
Code	Code39, 35cm	Code39, 35cm
Resolution	400	400
Speed	1/5	1/5
Material		
Temperature	-40 to 125	-40 to 125
Light Source	LED	LED
Power	20	20
Weight	ABS +	ABS +
Voltage	5V ± 5%	5V ± 5%
Power Consumption	375mW (peak); 226mW (idle); 750mW (max)	375mW (peak); 226mW (idle); 750mW (max)
Weight	145.0g ± 5g	145.0g ± 5g
Dimensions	164.5 * 91.5 * 68.0 mm	164.5 * 91.5 * 68.0 mm
Barcode	1D	1D
Barcode	1D	• 25 • 25 - 25
		• 39 • 39 - ASCII • 32
		• Code93 • Code93 - ASCII • Code128
		• EAN / GSL / UCC-128Auto • Codabar • MSI
		• EAN / JAN-13 • UPC-A • JAN-8 • Code11 • UPCE0
	2D	• MICRO QR • QR • AZTEC • PDF417

扫描角度	360° 30° 45°
支持的条码格式	Code39 4.17mil 15 6cm-12cm
	Code128 4.17mil 16 7cm-10cm
	10.83mil 8 bytes 5cm-16cm
	QR 1083mil 8 bytes 7cm-12cm
防护等级	
IP等级	IP52
工作温度	0 50°C / 32 122°F
存储温度	0 50°C / 32 122°F
工作湿度	20 85%
存储湿度	20 85%
静电防护	15KV
扫描距离	1.5m





OCBS-2018





OCBS-2018



▶ Company



▶ Certificates



▶ Payment



