

433 MHz kabelloser 32-Bit-Laser-Barcode-Scanner mit Halterung (Modell: OCBS-W800)

SPEZIFIKATIONEN:

PHYSIKALISCHE MERKMALE	
Lichtquelle:	Sichtbare Laserdiode (VLD) bei 650 nm
Scanner-Abmessungen :	168 mm * 72 mm * 93 mm (B * H * D)
Empfängerabmessungen:	130 mm * 45 mm * 129 mm (B * H * T)
Material:	ABS + TPR / Aluminiumlegierung
Gewicht:	370 g
Scanmodus:	Hand gehalten; Kontinuierlicher Scan-Modus.
Kontrollleuchte:	LED rot und blau
Summer:	Summer-Lautstärke einstellbar
LEISTUNGSMERKMALE	
Breite des Scanfeldes:	60mm @ 30mm □von der Motorfläche□ 98mm @ 100mm engine von der Motorfläche
Tiefe des Scanfeldes:	10-450mm □Kontrast 0,9 Dichte 0,25
Scangeschwindigkeit:	150 Scans / Sek
Scan-Präzision:	0,10-0,825 mm
Bit Fehlerrate:	1 / (5 Millionen)
Decodierfähigkeit:	UPC / EAN, UPC / EAN mit Ergänzungen, UCC / EAN128, Code 39, Code 39 voll ASCII, Trioptic Code 39, Code 128, Code 128 vollständig ASCII, Codabar, Interleaved 2 von 5, Diskret 2 von 5, Code 93, MSI, Code 11, RSS-Varianten, Chinesisch 2 von 5, MSI / Plessey, UK / Plessey, UCC / EAN 128, Chinesischer Code, GS1 DataBar (RSS) -Serie
Batterie:	3,7 V / 750 mAh, Li-Ion
Aufladezeit:	3,0 Stunden
Scan Zeit:	30 Stunden
Aktuell:	95mA (arbeitend); 25mA (Standby)
Winkel:	Steigung: 60 °; Neigung: 45 °
Arbeitsfrequenz:	433 MHz
Kommunikationsentfernung:	200m □Offene Orte□
Kommunikationsinterface:	USB
USER UMWELT-MERKMALE	
Temperatur:	-10 ° C bis 45Grad C (Betrieb), -40 ° C bis 60 ° C (Lagerung)
Relative Luftfeuchtigkeit:	5% -90% (nicht kondensierend)
Drop-Spezifikation:	Widersteht wiederholt 1,5 m Stürzen auf die Betonoberfläche
Umgebungsbeleuchtung:	0 ~ 100.000 LUX
Elektrostatische Entladung:	Entspricht einer Luftentladung von ± 12 kV und einer Kontaktentladung von ± 6 kV
Sicherheitszertifikat:	CE, FCC, Klasse 2, RoHS

Produktetails:



Wireless Barcode Scanner

OCBS-W800



Product Picture





Features

Simple but not easy



Integrated non-volatile memory

Data transmission distance reaches 200m in open area



Integrated non-volatile memory



Intelligent battery management system, real-time check the remaining battery



32bit decoder ensuring excellent decoding ability



All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
Memory	128K
Scanner Dimensions(W * H * D)	168mm * 72mm * 93mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	370g
Scanning Mode	Hand-held; Continuous Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	10-450mm (Contrast 0.9 Density 0.25)
Scan Speed	150 scans/sec

Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series
Battery	3.7V/750mAh, Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	95mA (working); 25mA(standby)
Angles	Pitch:60°; Tilt: 45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Communication Interface	USB
USER ENVIRONMENT CHARACTERISTICS	
Temperature	-10°C to 45°C (Operating), -40°C to 60°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at www.ocominc.com, Together we quest for the best.



Relevante Dokumente:

Möchten Sie mehr über das Produkt erfahren?Ormation?Bitte Klick hier.

[Spezifikation Handbuch](#)