Win CE PDA industrial basada

(Modelo: OCBS-D6000)

Pliego de condiciones:

Sistema operativo		Ventanas CE 5.0, SDK para múltiples lenguajes de programación, incluyendo C #, VB.net, VC ++ para ayudar desarrollador del sistema
UPC		SAMSUNG S3C2451 533MHZ
Memoria		RAM DDR2 128, M-ROM de 256 MB
Visualización		LED TFT QVGA pantalla táctil LCD a color de 2.8 pulgadas, resolución de 240 * 320
Teclado		27 teclas
Comunicación	Wifi (Por defecto)	Construido en 802 función de comunicación inalámbrica 11b / g, velocidad: 54MB / Sec, puede satisfacer CISCO Estándar de seguridad CCX2,3
	GPRS (Opcional)	Apoyo GSM / GPRS 10, GSM27,10
Datos colección (3 opciones)	1D escáner de código de barras	Láser de código de barras escáner, Velocidad de lectura: 100 scan / seg Código: UPC-A; UPC-E; UPC-E1; EAN-8; EAN-13; Libro EAN tierra; Código 128; UCC / EAN-128; Código 39; Código TRIOPTIC 39; Código 39 ASCII completo; Código 93; Código 11; Interleaved 2 de 5; Discrete 2 de 5; Bar Coda; MSI; GS1 Data Bar 14; GS1 Data Bar Limited; GS1 Data Bar Ampliado;
	2D Barcode Scanner	Código de barras 1D: UPC-A; UPC-E; UPC-E1; EAN-8; EAN-13; Libro EAN tierra; Código 128; UCC / EAN-128; Código 39; Código TRIOPTIC 39; Código 39 ASCII completo; Código 93; Código 11; Interleaved 2 de 5; Discrete 2 de 5; Bar Coda; MSI; GS1 Data Bar 14; GS1 Data Bar Limited; GS1 Data Bar Ampliado; Código de barras 2D: PDF417, MicroPDF417, Código Maxi, Maxi Code, Datos Matrix, códigos Composite & amp; Código QR,
	RFID	13.56MHZ, apoyo ISO15693, ISO14443A acuerdo / B
Energía	Batería	3.7V 2600MAH
	Espere tiempo	120 horas
	Trabajo tiempo	8 horas
Expandir puerto		Apoyo Micro SD / TF tarjeta de hasta 16 GB
Industrial grado		IP65
Dimensiones		169 (l) x 60 (W) x 31 (H) mm
Peso		320g (Incluyendo la batería)
Trabajo medio ambiente	Funcionar temperatura	-15 ~ + 50 Grado C
	Tienda temperatura	-20 ~ + 60 Grado C
	Funcionar humedad	5-95%
	Humedad tienda	5-95%
	Altura de Anti-sísmica	1.2m piso de cemento

Detalles del producto:

Product Picture

Features

Simple but not easy

Default configuration :Wifi+1D barcode scanner;

Bluetooth, GPRS communication for option;

2D scanner, 125K/134.2K/13.56M Hz RFID reader for options;

Win. CE 5.0 multi-language operation system;
Easy secondary development, compatible with different software;

RAM DDR2 128MB, F-ROM 256MB;
High capacity 2800mA battery and low consumption;

Industrial rugged design, water-proof and protection grade(IP65);

and protection grade(IP 65),

All-round show

Application Area

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Parameter

Operation system		Windows CE 5.0,SDK for multiple programming languages including C#, VB.net, VC++ to assist system developer
CPU		SAMSUNG S3C2451 533MHZ
Memory		RAM DDR2 128MB, F-ROM 256MB
Display		TFT-LED QVGA 2.8 inch LCD color touch screen, resolution 240*320
Keyboard		27 keys
	Wi-Fi (default)	Built in 802 11b/g wireless communication function, rate:

Communication		54MB/Sec, can meet CISCO CCX2,3 security standard
	GPRS(Optional)	Support GSM/GPRS 10,GSM27,10
Data collection (3 options)	1D barcode scanner	Laser Barcode scanner, Scan Rate: 100 scan/sec Code: UPC-A; UPC-E; UPC-E1; EAN-8; EAN-13; Book land EAN; Code 128; UCC/EAN-128; Code 39; Trioptic Code 39; Code 39 Full ASCII; Code 93; Code 11; Interleaved 2 of 5; Discrete 2 of 5; Coda bar; MSI; GS1 Data Bar 14; GS1 Data Bar Limited; GS1 Data Bar Expanded;
	2D Barcode Scanner	**1D barcode:** UPC-A; UPC-E; UPC-E1; EAN-8; EAN-13; Book land EAN; Code 128; UCC/EAN-128; Code 39; Trioptic Code 39; Code 39 Full ASCII; Code 93; Code 11; Interleaved 2 of 5; Discrete 2 of 5; Coda bar; MSI; GS1 Data Bar 14; GS1 Data Bar Limited; GS1 Data Bar Expanded; **2D barcode:** PDF417、microPDF417 ,Maxi Code, Maxi Code, Data Matrix, Composite Codes & QR Code,
	RFID	13.56MHZ, support ISO15693, ISO14443A/B agreement
Power	Battery	3.7V 2600MAH
	Standby time	120 hours
	Working time	8 hours
Expand port		Support Micro SD/TF card up to 16GB
Industrial grade		IP65
Dimensions		169(l)×60(W)×31(H) mm
Weight		320g (include battery)
Working environment	Operate temperature	-15~+50 Degree C
	Stock temperature	-20~+60 Degree C
	Operate humidity	5-95%
	Stock humidity	5-95%
	Height of Anti-seismic	1.2m cement floor

Production Line

Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

✓ *Indicates information has been verifed onsite by TUV on 2013.7.15*

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfication.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment.Some designated models can have as long as 24 months warranty.

Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

✓ *Indicates information has been verifed onsite by TUV on 2013.7.15*

Certifications

Packing and Shipment

Payment

WIRE TRANSFER | WESTERN UNION | MoneyGram. | ESCROW

LC | AliExpress | PayPal |

Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have estabilshed goods relationship with our customers and have friendly communication with each other.

Why you choose us?

Company Profile

OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals . Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Eruope, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.

Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China;
Websites: http://www.thermalprinter.com.cn ; http://www.ocominc.com ;
E-mail: ocom@ocominc.com , ocomtech@gmail.com ;
Skype: ocominc2000, ocominc;
MSN: ocomtech@hotmail.com, ocominc@hotmail.com;
Trademanager: szocominc, cn1500439666;
QQ: 2485890637,190852203;
Tel/Fax: +86.755.8605.3207.

Documentos importantes:

*Especificación

*OS_EN D6000

Videos Relacionados:

PF: