

Handheld 1D Laser Bar Code Reader Barcode Scanner

(Model No.: OCBS -L017)

Rasgo:

200MM/S Scan Speed;
10-40cm long depth of field;
Compatible with multiple language layout;
1.5m free fall on concrete surface;
Can switch to manual,continuous scanning.

Especificación:

General	
Modelo	OCBS -L017
Material	ABS+PVC+PC
Idioma	múltiples idiomas
Interfaz	USB
Trigger Mode	Manual , Continuous scanning
Operating Current	50mUN(Operating), 40mUN(Stand By), 100mUN(Max)
Fuente de alimentación	DC 5V±5%
Quiescent Current	20mA
ESD Protection	15KV air discharge
Resistencia a los golpes	1.5m free fall on concrete surface
Actuación	
Scan Speed	200 scans per second
Scanning Depth	2—9cm(0.1mm Width), 3—30cm(0.3mm Width)
Width of Scan	Min 0.1mm(4mils)
Print contrast	≥25%
Scanning Distance	10-400mm Roll 60°, Pitch45°
Fuente de luz	visible láser 650nm
Decode Capability	1D□UPC-A,UPC-E,EAN-8,EAN-13,Code 128, Code 39,Code 93, Interleaved 2 of 5,Matrix 2 of 5,Industrial 2 of 5, Standard 2 of 5(IATA25) ,Codabar□NW-7□,etc.
Físico	
Casing Size	150mm * 70mm * 95mm
Medioambiente	
Trabajando temperatura& humedad	0 to 45 grados centígrados, 10%~80% No condensation
Almacenamiento temperatura& humedad	-20 to 60 grados centígrados , 10%~90% No condensation

