

Pequeño Fijo Omnidireccional Laser Barcode Scanner (Modelo: OCBS-

T007

)

Pliego de condiciones:

| | |
|--|---|
| Parámetros de rendimiento | |
| Fuente de luz | 650 nm láser de diodo láser visible |
| Zumbador | Siete tonos o silencio |
| Lámpara | Azul = luz láser, listos para escáner, Rojo = decodificación éxito |
| Interfaz del sistema | PC kBW, RS232, USB |
| Parámetros físicos | |
| Volumen (Lx W x H) | Tamaño del producto (180 * 130 * 110 mm), Tamaño del embalaje: (230 mm * 160 mm * 120 mm) |
| Peso | Tamaño del producto (460 g), empaque (630 g) |
| Parámetros eléctricos | |
| Voltaje de entrada | 5VDC + / -10% |
| Energía del trabajo | 1000mW (200mAx5V) |
| Energía en espera | 900mW (180mAx5V) |
| Fuente de corriente continua | Clase 02:05 VDCx1A |
| Nivel láser | Class1 |
| Identificación | CE, RHOS, FCC Parte 15 Clase B, Unión Europea de EMC Directiva |
| Parámetro ambiental | |
| temperatura de funcionamiento | 0degree C - 40 grados C |
| Temperatura de almacenamiento | -40degree C-60degree C |
| Humedad | 5% a 95% humedad relativa (sin condensación) |
| Antiknock característica | Para soportar de 1,5 metros de altura de caída. |
| Opresión en polvo | Selle para evitar que el polvo del aire de la erosión de las partículas. |
| Parámetros de análisis | |
| El modo de exploración | Omnidireccional de 20 líneas |
| Velocidad de escaneo | 1.120 veces por segundo |
| Contraste de impresión | Mínimo 30% de diferencia reflexión |
| Rollo (inclinación), Inclinación, desviación (guiñada) | 360 °, 60 °, 60 ° |
| Capacidad de decodificación | UPC / EAN / JAN, Código 39Full ASCII, Code128Full ASCII, Codebar, Código 2 de 5, Code93, Code11, MSI Plessey, trióptico, GS1 Data Bar, Telepen. |

Detalles del producto:



The advertisement features the OCOM logo at the top left with the tagline "All your side". The main text, in green, reads "Omni-directional Laser Barcode Scanner OCBS-T007". A black scanner is shown on the right, and a person is blurred in the background. At the bottom right, there are several certification logos including CE, FCC, and others. A blue bar at the bottom contains the text "Product Picture" next to three vertical bars.

ocom
All your side

**Omni-directional
Laser Barcode Scanner
OCBS-T007**

CE FCC

Product Picture





Features

Small Size, BIG Performance

20 scanning lines and five directions;
1120 times per second reading speed;





Multiple/Single line scanning capability meet different requirements;
Multiple interfaces optional: KBW, RS232 or USB.



Blue LED lights, loud buzzer hints;
The base can rotate.





Appearance is concise and easy, stable performance.

All-round show





Parameter

| Performance parameters | |
|--------------------------------|---|
| Light source | 650 nm visible laser diode laser |
| buzzer | Seven tones or silent |
| lamp | Blue = laser light, ready to scanner, Red = decoding success |
| System interface | PC kBW,RS232,USB |
| Physical parameters | |
| volume(Lx W x H) | Product size (180 * 130 * 110 mm), packing size:(230 mm * 160 mm * 120 mm) |
| Weight | Product size (460 g), packing (630 g) |
| Electrical parameters | |
| Input voltage | 5VDC+/-10% |
| Work power | 1000mW(200mAx5V) |
| standby power | 900mW(180mAx5V) |
| direct-current source | Class 2:5VDCx1A |
| Laser level | Class1 |
| identification | CE,RHOS,FCC Part 15 Class B, European Union EMC Directive |
| Environmental parameter | |
| operating temperature | 0° C - 40° C |
| Storage Temperature | -40° C - 60° C |

| | |
|-----------------------------|--|
| humidity | 5% to 95% relative humidity (no condensation) |
| antiknock characteristic | To withstand from 1.5 meters high drop. |
| dust tightness | Seal to prevent air dust particle erosion. |
| Scanning parameters | |
| Scanning mode | Omni directional 20 line |
| Scanning speed | 1120 times per second |
| printing contrast | Minimum 30% reflection difference |
| Roll(tilt),Pitch, Skew(yaw) | 360°,60°,60° |
| Decoding ability | UPC/EAN/JAN, Code 39Full ASCII,Code128Full ASCII, Codebar, Code 2 of 5,Code93,Code11,MSI Plessey,Trioptic,GS1 Data Bar, Telepen. |

Applications

OCBS-T007 is an aggressive, omnidirectional presentation laser bar code scanner. Designed for applications where counter space is at a premium, OCBS-T007 is the ideal presentation scanner for **retail, convenience, liquor and specialty stores**. In addition, OCBS-T007 unique, contoured shape allows it to be picked up and used as a hand-held when scanning large or bulky items. Lightweight and rugged, OCBS-T007 is small in size but BIG in performance.



Production Line



Capacity

| Verified | Product Name | Production Line Capacity | Actual Units Produced(Previous Year) |
|----------|--------------------|--------------------------|--------------------------------------|
| ✓ | Thermal Printer | 40,000 Sets / Month | 250,000 Sets |
| ✓ | Dot Matrix Printer | 15,000 Sets / Month | 10,000 Sets |

| | | | |
|---|---------------------------------|---------------------|-------------|
| ✓ | Bluetooth Printer | 30,000 Sets / Month | 20,000 Sets |
| ✓ | Barcode Scanner | 40,000 Sets / Month | 20,000 Sets |
| ✓ | POS Machine | 5,000 Sets / Month | 10,000 Sets |
| ✓ | Magnetic Card Reader and Writer | 45,000 Sets / Month | 50,000 Sets |

✓ Indicates information has been verified onsite by TUV on 2013.7.15

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

| Verified | Machine Name | Brand & Model No. | Quantity |
|----------|--------------------------|-------------------|----------|
| ✓ | Ageing Tester | No information | 6 |
| ✓ | Withstand Voltage Tester | CC2670A | 1 |
| ✓ | Oscilloscope | TBS1102 | 1 |
| ✓ | DC Power Supply | PS-305DM | 6 |

| | | | |
|---|----------------------|----------------|----|
| ✓ | Digital Torque Meter | HP100 | 1 |
| ✓ | Calliper | GUANGLU | 2 |
| ✓ | Multi-meter | VC890D | 7 |
| ✓ | Test Computer | No Information | 13 |

✓ Indicates information has been verified onsite by TUV on 2013.7.15

Certifications



Packing and Shipment



Double wall corrugated board



Double outer cartons

Marks and fragile stickers



Outer protection film





Payment



Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?



Company Profile

This Assessed Supplier Has Been Independently Verified

Build Your Growth On Trust



TÜVRheinland®
Precisely Right.



OCOM Technologies Limited, founded in 2007, is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Europe, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation." We would like establish stable and reliable partnership with customers.

energy source, center for excellence, strategic cooperation. We extend our business global and provide products and solutions all over the world. OEM/ODM is welcome.



Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: 11/F, Tower A, New Energy Building, #2009, Nanhai Ave., Nanshan district, Shenzhen
Guangdong, 518054, China;

E-mail: ocom@ocominc.com, ocomtech@gmail.com ;

Skype: [ocominc2000](https://www.skype.com/user/ocominc2000), [ocominc](https://www.skype.com/user/ocominc);

MSN: [ocomtech@hotmail.com](https://www.hotmail.com/ocomtech), [ocominc@hotmail.com](https://www.hotmail.com/ocominc);

Trademanager: [szocominc](https://www.trademanager.com/szocominc), [cn1500439666](https://www.trademanager.com/cn1500439666);

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



Documentos pertinentes:

¿Quieres saber más inf productoormación?Por favor, Haga clic aquí. 

[Especificación](#)