

High Performance 1D/2D Barcode Scanner

(Model No.: OCBS-2021)

Feature:

- Subvert traditional design, with simple assembly stand
- 0.3 million overall situation exposure, 60fps fast speed,
- 3mil resolution bar code reading ability
- Support reading many kinds of 1D&2D bar code
- Support reading difficult bar codes (blurred, wrinkled, fuzzy, low contrast, high density, etc.)
- Widely used in different host systems, such as windows 7/8/10, iOS, Android and Linux system, etc.
- Most of application at retail stores, supermarket, chains, medical, luxury, clothing, jewelry, tobacco, etc.



Product specifications are subject to change without prior notice.

Together We Quest For The Best

OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: ocom@ocominc.com;

Tel/Fax: +86.755.8605.3207;

**Specification:**

Performance parameters	Model	OCBS-2021
	Image Sensor	CMOS
	Light Source	White LED(lighting) red LED aiming
	CPU	32bit ARM
	COMS Image Size	640x480
	Exposure	Global Exposure
	Scanning speed	60fps
	Resolution	≥3mil
	Decoding Depth	60-360mm
	Scan Angle	Rotate 360°, inclination 65°, elevation 60°
	Scanning mode	Manual trigger/automatic induction
Decoding ability	1D:Codabar、Code11、Code39、Code32、Interleaved 2 of 5、Industrial 2 of 5、Matrix 2 of 5、Code93、Code128、GS1-128、UPC-A、UPC-E、EAN 8、EAN 13、GS1 DataBar (RSS14)、GS1 DataBar Limited、GS1 DataBar Expanded、etc	
	2D: PDF417、Micro PDF417、QR Code、Micro QR、Data Matrix、Aztec Code	
Other parameters	Size	L*W*H= 163*68*80(mm)
	Weight	185g
	Material	ABS+TPU
	Input voltage	DC 3.6V-5.5V
	Working current	142mah
	Standby current	42mah
	Prompt	Beep&LED
	Interface	USB-HID、USB-VCP
	Cable standard	1.6m

Product specifications are subject to change without prior notice.

Together We Quest For The Best

OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan,
Shenzhen 518059, China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: ocom@ocominc.com;

Tel/Fax: +86.755.8605.3207;



	Working temperature	0°C – 50°C
	Working humidity	Relative humidity 5%-95%(no condensation)
	Storage temperature	-40°C – 70°C
	Anti-ambient light interference	0 – 5000Lux(fluorescent), 0 – 100,000Lux(Sunlight)

Product specifications are subject to change without prior notice.

Together We Quest For The Best