

80mm Auto-coupe thermique Imprimante ticket

(Modèle: OCPP-80L)

Spécifications:

| | |
|---------------------------|--|
| Procédé d'impression | Direct thermique |
| La vitesse d'impression | 200 mm / s |
| Largeur du papier | 79,5 ± 0,5 mm |
| Rouleau de papier | 80mm |
| L'épaisseur du papier | 0,06 ~ 0,08 mm |
| la capacité de la colonne | 576 points / ligne 512 points / ligne |
| La taille des caractères | ANK, Font A: points 12X24 B de la police: 9x17 points Simplifié / chinois traditionnel: 24X24 points |
| espace de Ligne | 3.75mm (modifiable en utilisant des commandes) |
| Interface | USB / LAN |
| Code-barres | UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODABAR / ITF / CODE39 / CODE93 / CODE128 |
| Code page | PC347 (Standard Europe), Katakana, PC850 (multilingue), P C860 (portugais), PC863 (canadien-français), PC865 (nordique), Europe de l'Ouest, le grec, l'hébreu, l'Est L'Europe, l'Iran, WPC1252, PC866 (cyrillique 2 #), PC852 (Latin2), PC858, Iranll, Letton, arabe, PT151 (1251) |
| Cutter automatique | Plein / partiel (facultatif) |
| NV FLASH | 256K Octets |
| tampon d'entrée | 64K Octets |
| Source de courant | DC 24V-2.5A |
| contrôle de tiroir-caisse | DC 24V-1A |
| Fiabilité | Impression tête vie: 100 km vie de coupe automatique: 1 million de coupes |
| Environnement de travail | Température (0 ~ 45 degrés C), l'humidité (10 ~ 80%) |
| Environnement de stockage | Température (-10 ~ 60 degrés C), l'humidité (10 ~ 90%) |
| Pilotes | Victoire 9X / Win 2000 / XP Win / Win 7 / Win 8 / Win 8.1 / Linux |
| Commandement | Compatible avec ESC / POS |
| Poids brut | 1,3 kg |
| Dimension | 183x143.5x135mm (L x L x H) |

Détails du produit:



ocom
All your side

**80mm Terminal Receipt Printer
with Auto-cutter
OCPP-80L**

Product Picture





Features

Simple but not easy

Easy to operate and open the cover,
convenient for maintenance;



High resolution printer and reliable quality



High resolution printing and reliable quality;

Avoid order missing;
Compatible with ESC/POS command;



Variety of applications:
hotels, catering, entertainment, logistics,
health care, and other industries;



All-round show





Application Area

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf



Parameter

| | |
|-----------------|----------------|
| Printing method | Direct thermal |
| Printing speed | 200mm/s |
| Paper width | 79.5±0.5mm |
| Roll paper | 80mm |
| Paper thickness | 0.06-0.08mm |

| | |
|----------------------------|--|
| Column capacity | 576 dots/line 512 dots/line |
| Character size | ANK, Font A:12X24 dots Font B:9X17 dots Simplified/traditional Chinese: 24X24 dots |
| Line space | 3.75mm(changeable using commands) |
| Interface | USB/LAN |
| Bar code | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128 |
| Code page | PC347(Standard Europe), Katakana, PC850(Multilingual), P C860(Portuguese), PC863(Canadian-French), PC865(Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), PC858, IranII , Latvian, Arabic, PT151(1251) |
| Auto cutter | Full/Partial(optional) |
| NV FLASH | 256K Bytes |
| Input buffer | 64K Bytes |
| Power supply | DC 24V-2.5A |
| Cash drawer control | DC 24V-1A |
| Reliability | Printing head life: 100km Auto cutter life: 1 million cuts |
| Working environment | Temperature (0~45 Degree C), humidity (10~80%) |
| Storage environment | Temperature (-10~60 Degree C), humidity (10~90%) |
| Drivers | Win 9X/Win 2000/Win XP/Win 7/Win 8/Win 8.1/Linux |
| Command | Compatible with ESC/POS |
| Gross weight | 1.3kg |
| Dimension | 183x143.5x135mm(L x W x H) |

Production Line



Capacity

| Verified | Product Name | Production Line Capacity | Actual Units Produced(Previous Year) |
|----------|---------------------------------|--------------------------|--------------------------------------|
| ✓ | Thermal Printer | 40,000 Sets / Month | 250,000 Sets |
| ✓ | Dot Matrix Printer | 15,000 Sets / Month | 10,000 Sets |
| ✓ | Bluetooth Printer | 30,000 Sets / Month | 20,000 Sets |
| ✓ | Barcode Scanner | 40,000 Sets / Month | 20,000 Sets |
| ✓ | POS Machine | 5,000 Sets / Month | 10,000 Sets |
| ✓ | Magnetic Card Reader and Writer | 45,000 Sets / Month | 50,000 Sets |

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

| Verified | Machine Name | Brand & Model No. | Quantity |
|----------|--------------------------|-------------------|----------|
| ✓ | Ageing Tester | No Information | 6 |
| ✓ | Withstand Voltage Tester | CC2670A | 1 |
| ✓ | Oscilloscope | TBS1102 | 1 |
| ✓ | DC Power Supply | PS-305DM | 6 |
| ✓ | Digital Torque Meter | HP100 | 1 |
| ✓ | Calliper | GUANGLU | 2 |
| ✓ | Multi-meter | VC890D | 7 |
| ✓ | Test Computer | No Information | 13 |

Certifications



Packing and Shipment



Payment





Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?



Company Profile

This Assessed Supplier Has Been Independently Verified

Build Your Growth On Trust



TÜV Rheinland





FOV Hengman
Precisely Right.



OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Europe, Australia, Asia, and other area.



OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,
Shenzhen 518054, China;

Websites: <http://www.thermalprinter.com.cn> ; <http://www.ocominc.com> ;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



Documents pertinents:

[*Spécification](#)

[*IP Manuel Configurer adresse](#)

[*Manuel d'instruction](#)

[* Pilote pour tous les système Windows](#)

[*Pilote pour Linux](#)

[*Paramètres de l'imprimante Réglage Outils](#)

[*CD Fichiers](#)