

φορητ??

ασύρματο Barcode Scanner

(Μοντέλο:OCBs-W700)

ΠΡΟΔΙΑΓΡΑΦΕΣ:

ΦΥΣΙΚΕΣ characteristics	
Πηγή φωτός:	Ορατό κόκκινο λέιζερ 650 nm
Scanner Διαστάσεις:	160 χιλιοστά * 70 χιλιοστά * 40 χιλιοστά(W * H * D)
Βάρος:	300G
Υλικό:	ABS + PC
Τρόπος ανίχνευσης:	Μια σάρωση γραμμή? Χειροκίνητη / Αυτόματη
Δείκτης Way:	Buzzer και ενδεικτική λυχνία
Characterstics ΑΠΟΔΟΣΗΣ	
Πλάτος σάρωσης Πεδίο:	20 χιλιοστά @ σαρωτή παράθυρο 260 χιλιοστά @ 260 χιλιοστών
Βάθος σάρωσης Πεδίο:	4mil (0,1 χιλιοστά) / 5-60 χιλιοστά 5mil (0,12 χιλιοστά) / 10 100 μm 10mil (0,25 χιλιοστά) / 15-250mm 35mil (0,89 χιλιοστά) / 140-600mm 43mil (1,1 χιλιοστά) / 150-800 χιλιοστών
Ταχύτητα Σάρωσης:	120 ανιχνεύσεις / δευτερόλεπτο
Σάρωση ακριβείας:	0,10 χιλιοστών (pcs0.9)
Εκτύπωση Αντίθεση:	Τουλάχιστον 30% διαφορά αντανάκλαση
Error Rate:	1 / (6 εκατ.)
Decode Capability:	Διεθνής γενική 1D barcodes
Τρέχουσα:	60mA (εργασίας)? 5uA (σε κατάσταση αναμονής)
Σάρωση Corner:	32 °
Σάρωση Υψόμετρο:	68 °
Σάρωση Γωνία Avertence:	52 °
Συχνότητα Λειτουργίας:	2.4GHz
Απόσταση ανακοίνωση:	100m (Ανοίξτε μέρος) 20m (Indoor)
Επικοινωνία Interface:	USB
Characterstics ΠΕΡΙΒΑΛΛΟΝ ΧΡΗΣΤΗ	
Drop Προδιαγραφές:	2m ελεύθερη πτώση
Επίπεδο Laser:	Επίπεδο-1 πρότυπο ασφάλειας λέιζερ
Φορτίστε Ισχύς:	DC5V

Λεπτομέρειες:



Wireless Barcode Scanner

OCPP-W700

Product Picture





Features

Simple but not easy

Integrated non-volatile memory (can store about 500 barcodes);



Outside communication distance can



reach 100m, inside is 20m;;

20 scanners can work in the same field without interfering each other;



Plug and play;



800mA big capacity Li-battery.



||| All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Red Laser 650 nm
Scanner Dimensions(W * H * D)	160mm * 70mm * 40mm
Weight	300G
Material	ABS + PC
Scanning Mode	One line scanning; Manual / Automatic
Indicator Way	Buzzer and Indicator Light
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	20mm@scanner window 260mm@260mm
Depth of Scan Field	4mil (0.1mm)/5-60mm 5mil (0.12mm)/10-100mm 10mil (0.25mm)/15-250mm 35mil (0.89mm)/140-600mm 43mil (1.1mm)/150-800mm

Scan Speed	120 scans/sec
Scan Precision	0.10mm (pcs0.9)
Printing Contrast	Minimum 30% reflection difference
Error Rate	1/(6million)
Decode Capability	International general 1D barcodes
Current	60mA (working); \leq 5uA(standby)
Scanning Corner	32°
Scanning Elevation	68°
Scanning Angle of Avertence	52°
Working Frequency	2.4GHz
Communication Distance	100m (Open Places) 20m (Indoor)
Communication Interface	USB
USER ENVIRONMENT CHARACTERISTICS	
Drop Specification	2m free fall
Laser Level	Level-1 laser safety standard
Charge Power	5VDC

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



© 2012-2013 All rights reserved. | www.ocominc.com



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.



Σχετικά έγγραφα:

Θέλετε να μάθετε περισσότερα inf προϊόνormation; Παρακαλώ Κάντε κλικ εδώ.

[Προσδιορισμός](#)