## 433MHz&Bluetooth Wireless 2D Barcode Scanner

(ModelNo.: OCBS-W232)

## FEATURE:

 $\ensuremath{n}$  Integrated non-volatile memory;

- ${\rm n}$  32bit decoder ensuring excellent decoding ability;
- $n \ \mbox{Compatible}$  with both Bluetooth and 433MHZ wireless communications;
- $n\,$  433MHz wireless data transmission distance reaches 200m in open area;
- $n\,$  Bluetooth wireless data transmission distance reaches 15m;
- n 433MHz wireless receiver can workswith 100 scanners ;
- $\ensuremath{n}$  Simple pairing mode, the user ismore convenient;
- n Intelligent batterymanagement system, real-time check the remaining battery;

PHYSICAL CHARACTERSTICS	
Scan mode	Image type
Memory	128K
Scanner Dimensions(W * H	
* D)	168mm * 72mm * 93mm
Receiver Dimensions(W * H	
* D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	370g
Scanning Mode	Hand-held; Continuous Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERSTICS	
Depth of Scan Field	10-450mm Contrast 0.9 Density 0.25
Scan Speed	300 scans/sec
Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series,QR CODE,PDF417,DATAMATRIX
Battery Charge Time Scan Time	3.7V/750mAh,Li-ion 3.0 Hours 30 Hours

## SPECIFICATION:

Current	95mA (working); 25mA(standby)
Angles	Pitch:60°; Tilt: 45°
Working Frequency	433MHz or Bluetooth
Base Interface	USB
USER ENVIRONMENT CHAR	<b>ACTERSTICS</b>
Temperature Relative Humidity Drop Specification Ambient Illumination Electrostatic Discharge Safety Certificate	-10 degree C to 45 degree C (Operating), -40 degree Cto 60 degree C (Storage) 5%-90%(Non-Condensing) Withstands repeated 1.5m drops to concrete surface $0 \sim 100,000 LUX$ Conforms to ±12KV air discharge and ±6KV of contact discharge CE, FCC, Class 2, RoHS



## OCBS-W232

