

Model	POS-1519
Name	15.1 inch all in one touch POS terminal
Housing	Plastic shell machine body and aluminium base
Color	whole black color machine
Main screen	15.1 inch touch screen monitor
Resolution	1024*768
Brightness	2 250cd/m
View angle	Horizon: 150; Vertical :140
Touch screen	Multi-point projected G+G capacitive touch
Sub-display	15.1 inch display or 12.1inch display W/o touch function for option
Customer display	2*20 VFD or 2*20 LCD display mounted to back cover for option
Performance	
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz, or Intel Celeron J4125,intel core I3 / I5 CPU for option
System Memory	1*SO-DIMM DDRIII slot, 4GB DDR3L/1333, 8GB for option
Storage device	M SATA SSD 64GB or higher, up to 256GB
Audio	On board Real Tek ALC662
LAN	10/100Mbps, Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module
Operating System	Windows7/8/10, Embedded,WEPOS,Linux
Connectivity	
External I/O port J1900	power button*1,12V DC in Jack*1
	LAN:RJ-45*1
	USB*6
	15PIN D-sub VGA *1
	RS 232*2
	line out*1,MIC in*1
Options	
MSR	optional side MSR
Package	
Weight	Net 6.5Kg, Gross 8.0Kg for single screen
Package with foam inside	425*275*405mm for single screen, 440*295*425mm for dual screen
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Accessories	
Power adapter	200-240V/50-60HZ(default) , 110-240V/50-60HZ AC power input ,DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available

Application



Bar



Restaurant



Coffee Store



Mile Tea Store



Bakery



Convenience Store



Library



Supermarket