

58 millimetri Mini ad alta velocità di stampa della stampante termica per ricevute (Modello: OCPP-585)

Specifica:

Metodo di stampa	termica diretta
Densità di stampa	384dots / linea (203DPI)
Dimensioni caratteri	384dots / linea, carattere ANK, caratteri: A: 12 * 24dots, 1.5 (W) * 3.0 (H) mm Semplificato / tradizionale: 24 * 24dots, 3.0 (W) * 3.0 (H) mm
Tipo di codici a barre	JAN13(EAN13)JAN8(EAN8)CODE39 QR (opzionale)
comando stampa	Compatibile con PSON ESC / POS
Lingua	supporto per la lingua del compratore
Velocità di stampa	90 millimetri / sec
Larghezza carta	57,5 ± 0,5 millimetri
Spessore carta	0.06-0.08mm
MCBF (la vita)	50 km
Dimensione	190 * 132 * 119 millimetri
Peso lordo	1.2KG
taglierina automatica	taglierina manuale
Sensore	Carta Near End Sensor, carta Fine Sensor, sensore di apertura della copertura
Rotolo di carta	Φ75mm
Interfaccia	RS-232C, parallela, USB, LAN
autista	Win 9X, wIN 2000, 2003 di vittoria, Win XP, Win Vista, Win 7 compatibile con ESPON
Ingresso adattatore di tensione	AC 110V / 220V, 50-60hz
Uscita adattatore di tensione	DC12V / 3A
Stampante Tensione di ingresso	DC12V / 3A
Controllo Cassetto contanti	DC12V / 1A
Temperatura di lavoro	0-45°C, Umidità: 10-80%
Salvataggio Temperatura	-10-60°C, Umidità: 10-90%
Certificato	CE / FCC / CCC / RoHS

Dettagli del prodotto:



**58mm Thermal
Receipt Printer**
OCP-585



Product Picture





Features

Simple but not easy

Small size and elegant design





High printing speed



Compatible with ESPON



Can drive cash drawer



Printing head life: 50KM



All-round show





Application Area

Food delivery, restaurant, Traffic Citation,
Logistics, Transportation, Warehouse management,
Delivery, Illegal Parking Ticket, Drugstore,
Price Tag, Retail/Farm



Parameter

Printing Method	Direct thermal
Print Density	384dots/line (203DPI)
Character Size	384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Barcode Type	JAN13 (EAN13) JAN8 (EAN8) CODE39
Printing Command	Compatible with EPSON ESC/POS
Language	Buyer language support
Printing Speed	90mm/sec
Paper Width	57.5±0.5mm
Paper Thickness	0.06-0.08mm
MCBF(life)	50km
Dimension	190*132*119mm
Gross Weight	1.2KG
Auto Cutter	manual cutter
Sensor	Paper Near End Sensor, Paper End Sensor, Cover open sensor
Roll Paper	Φ75mm
Interface	RS-232C, Parallel, USB, LAN
Driver	Win 9X, Win 2000, Win 2003, Win XP, Win Vista, Win 7 compatible with ESPON
Adapter Voltage Input	AC 110V/220V, 50-60Hz

Adapter Voltage Output	DC12V/3A
Printer Input Voltage	DC12V/3A
Cash Drawer Control	DC12V/1A
Working Temperature	0-45℃, Humidity: 10-80%
Saving Temperature	-10-60℃, Humidity: 10-90%
Certificate	CE/FCC/CCC/RoHS

Paper Roll Installation



- A Open the printer cover.
- B Install the roller in the roll paper, and put them into the printer.
- C Pull out some paper outside the printer and then close the printer cover.
- D Close the top cover. Press the printer cover to avoid error position of roll paper.
- E Tear-off the paper correctly.

Connection



- a. Plug the DC cord connector into the printer's power connector..
- b. Plug the data cable connector into the printer's interface connector.
- c. Plug the drawer cable into the drawer kick-out connector on the back of the printer next to the interface connector.

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive

3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.



Documenti rilevanti:

[*specificazione](#)

[*Manuale di programma](#)

[*Manuale di istruzioni](#)

[* Driver per Windows](#)

[*Driver per Linux](#)

[*Parametri stampante attrezzi di regolazione](#)

[*Printdemo USB\(Application Software demo\)](#)

[*SDK per Android](#)

[*CD File](#)