

# Stampante per etichette a barre a barre termica diretta da 4 "

(Modello: OCBP -007A)

## Caratteristiche:

Design a celmshell a doppia qualità di alta qualità

CPU RISC a 32 bit

8 MB SDRAM, 4 MB Flash

Sensore di testa

203 Risoluzione DPI.

Velocità di stampa alta 102mm (4 " ") / s

Larghezza di stampa da 108 mm.

20-112mm (0.78 "-4.4") Larghezza media regolabile

## Specifiche:

|   |  |
|---|--|
| Parametro                               |  |
| Risoluzione                             | 8 punti / mm (203DPI)  |
| Metodo di stampa                        | Termico diretto  |
| Max.Print Speed.                        | 102 mm (4 ") / s   |
| Max.print width.                        | 108 mm (4,25 ")  |
| Lunghezza max.print.                    | 2286 mm (90 ")   |
| Tipo di supporto                        | Continuo, Gap, Black Mark, Fan-fold e foro perforato   |
| Larghezza media                         | 20-112mm (0.78 "-4.4")   |
| Spessore dei media                      | 0,06 ~ 0,16mm ((2,36 ~ 6.3Mil)   |
| Lunghezza dell'etichetta                | 10 ~ 2.286mm (0.4 " " ~ 90 " "   |
| Capacità del rotolo dell'etichetta      | 127 mm (5 ") od (ferita esterna)   |
| Allegato                                | Plastica a pareti a doppia parete  |
| Dimensione fisica                       | 240 mm (W) x 211 mm (h) x 166 mm (D)   |
| Peso                                    | 2.15kg.  |
| Processore                              | CPU RISC a 32 bit  |
| Memoria                                 | Memoria flash da 4 MB, 8 MB SDRAM, lettore di schede SD per espansione della memoria flash, fino a 4 GB  |
| Interfaccia                             | USB 2.0.   |
| Font interni                            | 8 font bitmap alfa-numerici, caratteri Windows sono scaricabili dal software.  |
| Codice a barre                          | 1D Bar Codice: Codice 39, Codice 93, Codice 128CC, Codice 128 Struments A, B, C, BodAbar, Interleaved 2 di 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN e UPC 2 (5) componenti aggiuntivi, MSI, Plessey, POS TNET, Cina POS T<br>2D Bar Code: PDF-417, Maxicode, Datamatrix, QR Code |
| Rotazione del font e del codice a barre | 0 °, 90 °, 180 °, 270 °  |
| Condizione dell'ambiente                | Funzionamento: 5 ~ 40 ° C, 25 ~ 85% Non condensazione, Conservazione: -40 ~ 60 ° C, 10 ~ 90% Non condensazione   |

**Descrizione del prodotto:**



Direct Thermal Barcode Label Printer  
OCBP-007

Product Picture



Parameter

|                           |   |
|---------------------------|---|
| Resolution                | 8 dots/mm(203DPI)   |
| Printing method           | Direct Thermal  |
| Max. print speed          | 102 mm (4")/S   |
| Max. print width          | 108 mm (4.26")  |
| Max. print length         | 2286 mm (90")   |
| Media type                | Continuous, gap, black mark, fan-fold and punched hole  |
| Media width               | 20-112mm (0.78"-4.4")   |
| Media thickness           | 0.06-0.16mm(2.36-6.3mil)  |
| Label length              | 10-2,286mm(0.4"-90")  |
| Label roll capacity       | 127 mm (5") OD (outside wound)  |
| Enclosure                 | Double-walled plastic   |
| Physical dimension        | 240 mm (W) × 211 mm (H) × 168 mm (D)  |
| Weight                    | 2.15kg  |
| Processor                 | 32-bit RISC CPU   |
| Memory                    | 4MB Flash Memory, 8MB SDRAM, SD card reader for Flash memory expansion, up to 4 GB  |
| Interface                 | USB 2.0   |
| Internal fonts            | 8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.   |
| Barcode                   | 1D bar code : Code 39, Code 93, Code 128(UCC, Code 128 subsets A, B, C, Codebar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPCA, UPEC, EAN and UPC (2/5) digits add-on, MSI, FLESSEY, POSTNET, China POST<br>2D bar code : PDF-417, Maxicode, DataMatrix, QR code |
| Font and barcode rotation | 0°, 90°, 180°, 270°   |
| Environment condition     | Operation: 5 ~ 40°C, 25 ~ 85% non-condensing, Storage: -40 ~ 60°C, 10 ~ 90% non-condensing  |



Features

32-bit RISC CPU, 8MB SDRAM, 4MB Flash;



20-108mm printing width adjustable;



Support PDF417, QR CODE, DOTMATRIX;



Support USB, Serial, LAN(OPTION);

All-round show



Application Area

Production Line



Capacity

| Verified | Product Name                    | Production Line Capacity | Actual Units Produced(Previous Year) |
|----------|---------------------------------|--------------------------|--------------------------------------|
| ✓        | Thermal Printer                 | 40,000 Sets / Month      | 250,000 Sets                         |
| ✓        | Dot Matrix Printer              | 15,000 Sets / Month      | 10,000 Sets                          |
| ✓        | Bluetooth Printer               | 30,000 Sets / Month      | 20,000 Sets                          |
| ✓        | Barcode Scanner                 | 40,000 Sets / Month      | 20,000 Sets                          |
| ✓        | POS Machine                     | 5,000 Sets / Month       | 10,000 Sets                          |
| ✓        | Magnetic Card Reader and Writer | 45,000 Sets / Month      | 50,000 Sets                          |

Indicates information has been verified onsite by TÜV on 2022.12.5

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

| Verified | Machine Name             | Brand & Model No. | Quantity |
|----------|--------------------------|-------------------|----------|
| ✓        | Aging Tester             | No information    | 6        |
| ✓        | Withstand Voltage Tester | CC2070A           | 1        |
| ✓        | Oscilloscope             | TRF1102           | 1        |
| ✓        | DC Power Supply          | PS-3550M          | 4        |
| ✓        | Digital Torque Meter     | HP100             | 1        |
| ✓        | Calliper                 | GUANGLIU          | 2        |
| ✓        | Multi-master             | VCR90D            | 7        |
| ✓        | Test Computer            | No information    | 13       |

Indicates information has been verified onsite by TÜV on 2022.12.5

Certifications



Packing and Shipment



**Payment**



**Customers Reference**

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.



**Why you choose us?**



**Company Profile**

**This Assessed Supplier Has Been Independently Verified**

Build Your Growth On Trust

**TÜVRheinland**  
Precision Right

OCOM Technologies (Shenzhen) founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, POS peripherals. Our products have passed CE, FCC, RoHS and other related certificates, and had testing in Europe, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years. All of the sales have more than 8 years' experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.



**Contact us**

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China.

Website: <http://www.possolution.com.cn>; <http://www.ocominc.com>;

E-mail: [ocom@ocominc.com](mailto:ocom@ocominc.com); [ocomtech@gmail.com](mailto:ocomtech@gmail.com);

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500436666;

QQ: 2485890637, 190852203;

Tel/Fax: +86 755 8605 3207.



## **Documenti rilevanti:**

[OCOM Label Stampante software e driver](#)