Ultime handfree 2d immaging barcode scanner

Può leggere l'acquisizione delle immagini e la decodifica

Scansione omnidirezionale, facile da scansione Desktop flatbed & amp; Disegno conciso Con costante supporto & amp; modulo scanner affidabile Acquisizione di immagini ad alta velocità e la decodifica

D			
Parametri di prestazione			
Fonte di luce	LED bianco		
Cicalino	Sette toni o silenziosa		
Lampada	Bianco		
Interfaccia di sistema	KBW, RS232, USB		
Parametri fisici			
Volume (Lx P x A)	Formato del prodotto 78 millimetri x 75 mm x 141 millimetri (3.2" x 3.3" x 5.9"),		
Peso	Size180 prodotto g (12 once)		
Parametri elettrici			
Tensione di ingresso	5.5 VDC ± 0.25 V		
Potenza di lavoro	2,0 W (430 mA a 5 V)		
In standby	0,5 W (100 mA a 5 V)		
Parametro ambientale			
Temperatura di esercizio	0 ° C - 40 ° C		
Temperatura Di	-40 ° C -60 ° C		
Conservazione			
Umidità	0% al 95% di umidità relativa (senza condensa)		
Antidetonante caratteristica	Resistere alta 1,5 metri caduta dal pavimento di cemento.		
Antipolvere	Sigillare per evitare che la polvere dell'aria erosione delle particelle.		
Parametri scansione			
Modalità di scansione	Omnidirezionale (640X480)		
Più alta riflettività	Max 20% riflettività può essere letto		
Angolo di scansione	70 °, 75 °		



Hand free Imaging Scanner for2D Barcode

OCBS-T201













Product Picture





Reliable with good price

High speed image acquisition and decoding





Can read the barcode on the screen

Omni-directional scanning, easy to scan





With steady stand & reliable scanner module

Desktop flatbed& Concise design





Bookstore



Supermakte



Pharmacy







Restaurant

Performance parameters			
Light source	white LED		
Buzzer	Seven tones or silent		
Lamp	White		
System interface	KBW, RS232,USB		
Physical parameters			
Volume(Lx W x H)	Product size 78 mm x 75 mm x 141mm (3.2" x 3.3" x 5.9"),		
Weight	Product size180 g (12 oz)		
Electrical parameters	The state of the s		
Input voltage	5.5 VDC ± 0.25 V		
Work power	2.0 W (430 mA @ 5 V)		
Standby power	0.5 W (100 mA @ 5 V)		
Environmental parameter	AV.		
Operating temperature	0° C - 40° C		
Storage Temperature	-40°C -60°C		
Humidity	0% to 95% relative humidity (no condensation)		
Antiknock characteristic	Withstand 1.5 meters high drop from concrete floor.		
Dust-proof	Seal to prevent air dust particle erosion.		
Scanning parameters	*		
Scanning mode	Omni directional (640X480)		
Highest Reflectivity	Max 20% reflectivity can be read		
Scanning Angle	70°, 75°		





OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers'satisfaction.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services.

OCOM's products have passed CE, FCC, TUV, RoHs and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments:

✓ Indicates information has been verified onsite by a certification specialist.

Test Equipment and Facilities

Verified	Machine Name	Brand & Model No.	Quantit
V	Ageing Tester	No Information	6
V	Withstand Voltage Tester	CC2670A	1
1	Oscilloscope	TBS1102	1
1	DC Power Supply	PS-305DM	6
1	Digital Torque Meter	HP100	1
1	Calliper	GUANGLU	2
1	Multi-meter	VC890D	7
1	Test Computer	No Information	13

Verified by TUV on 2013.7.15

Certification:









- · All products' warranty are not less than 12 month, some models even up to 24 months warranty.
- Spare parts will be provided for mass orders for customers' local maintenance.
- Any product found to be defective within 30 days of shipment shall be deemed Dead on Arrival (DOA). DOA products will be advance replaced and shipped via express.
- Have distributors or authorized agents in the main market who can provide local repair and replacement services.
- Professional CRM management insures fast respond for customer's enquiries and orders tracking.
- Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility.
- 7*24 hours online, responds with 12 hours in working days, and within 24 hours for rest days.

Packing and Shipment:





Payment:









secure payment







Trade Assurance

Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.



Company Profile




TRADE ASSURANCE

- ○100% money refund for Late shipment&Quality problem
- Guarantee on-time delivery
- Third-party pre-shipment quality inspection (Optional)
- No transaction commission charged
- The HIGHESTassurance amount guaranteed by alibaba

in the Auto-ID and POS industry .



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers, Thermal Printer, Barcode printer, Dot Matrix Printer, Barcode Scanner, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.













Why you choose us?





Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan

District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn; E-mail: ocom@ocominc.com, info@possolution.com.cn;

Tel: +86.755.86053207 ext 800; Fax: +86.755.86053207 ext 868; QQ: 2485890637, 190852203; Wechat: szocominc, hj34924238; Whatsapp: 008613352932860;



Relevant documents:

user manual