

Scanner di codici a barre laser wireless a 24 GHz
(Modello: OCBS -W600)

SPECIFICA:

CARATTERISTICHE FISICHE	
Fonte di luce:	Diodo laser visibile (VLD) @ 650 nm-670 nm
Dimensioni dello scanner:	164 mm * 67 mm * 95 mm(L * A * P)
Dimensioni del ricevitore:	130 mm * 45 mm * 129 mm(L * A * P)
Materiale:	ABS + TPR / lega di alluminio
Peso:	235g
Modalità di scansione:	Tenuto in mano; modalità di scansione bidirezionale.
Spia:	LED rosso e blu
Cicalino:	Volume del cicalino regolabile
CARATTERISTICHE PRESTAZIONALI	
Larghezza del campo di scansione:	60 mm a 30 mm □ Dalla faccia del motore □ 98 mm a 100 mm □ dalla faccia del motore □
Profondità del campo di scansione:	2,5-600 mm □ Contrasto 0,9 Densità 0,25 □
Velocità di scansione:	100 scansioni / sec
Precisione di scansione:	0,10 mm □ 4mil □ PCS0.9
Tasso di errore di bit:	1 / (5 milioni)
Capacità di decodifica:	UPC / EAN, UPC / EAN con supplementi, UCC / EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Codice 11, varianti RSS, cinese 2 di 5
Batteria:	3,7 V / 750 mAh, ioni di litio
Tempo di ricarica:	3.0 ore
Tempo di scansione:	30 ore
Attuale:	100mA (funzionante); 40mA (standby)
Angoli:	Inclinazione: 60 °; Inclinazione: 45 °
Distanza di comunicazione:	30m
Frequenza di lavoro:	2.4G
Memoria	16 MB
Interfaccia di comunicazione:	USB
CARATTERISTICHE DELL'AMBIENTE UTENTE	
Temperatura:	0grado C a 50grado C (Operativo), -40grado Ca 70 grado C (Conservazione)
Umidità relativa:	5% -90% (senza condensa)
Specifiche di goccia:	Resiste a ripetute cadute di 1,5 m su superfici in calcestruzzo
Illuminazione ambientale:	0 ~ 100.000 LUX
Scarica elettrostatica:	Conforme a ±12KV scarico aria e ±6KV di scarica dei contatti
Certificato di sicurezza:	CE, FCC, Classe 2, RoHS

Dettagli del prodotto:





Features

Simple but not easy

2.4 G wireless laser barcode scanner



Scan Speed: 100scans/sec



Scan speed: 10000/second

Data transmission distance reaches 30m in open area;



Scan Time: 30hours



||| All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm-670nm
Scanner Dimensions(W * H * D)	164mm * 67mm * 95mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	235g
Scanning Mode	Hand-held; bidirectional Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	2.5-600mm (Contrast 0.9 Density 0.25)
Scan Speed	100 scans/sec
Scan Precision	0.10mm (4mil) PCS0.9
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5
Battery	3.7V/750mAh,Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	100mA (working); 40mA(standby)

Angles	Pitch:60°; Tilt: 45°
Communication Distance	30m
Memory	2.4G
Communication Interface	USB ,RS232,PS2
USER ENVIRONMENT CHARACTERISTICS	
Temperature	0°C to 50°C (Operating), -40°C to 70°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.





We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.



Documenti rilevanti:

Per ulteriori informazioni sul prodotto, fare clic qui.

[Specifica](#)