

30x2 karakters Dubbel regelig LCD klantendisplay

(Modelnr.:OCPD-LCD230C-C1)

Kenmerken:

Ondersteunt 11 opdrachtmodi, waaronder EPSON enz.

Compatibel met 95 nationale talen;

Voeding van 5V tot 24V om onzinnig gebruik van onjuiste stroomtoevoer te voorkomen;

Kan 2 regels * 30 kolommen of 2 regels * 15 Chinees weergeven;

O POS / J POS-driver is standaard.

Data papier:

Algemeen	Weergavemethode	TN-LCD negatief display (wit op de blauwe achtergrond)
	karakters	30 kolommen * 2 regels of 20 Chinees * 2 regels
	helderheid	1200cd / m2
	Teken lettertype	Matrix van 16 * 16 punten
	Karakter type	95 alfanumeriek, 32 internationale tekens
	Karaktergrootte	9,92 [H] x 4,75 [B] mm [Chinees: 9,92 * 9,5 mm]
	Puntgrootte [X x Y]	0,426 (H) x 0,6 (V) mm
	Venstergrootte	142,7 (H) x 19,82 (V) mm
	PCB-grootte	160 [L] x 36,6 [B] x 10,1 [H] mm
Gewicht	Ongeveer 65,5 gram	
Opdrachtmodus	LD220, EPSON POS D101, AEDEX, UTC / S, UTC / P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL	
Taalondersteuning	FRANKRIJK [] DUITSLAND [] VK [] DENEMARKEN [] ZWENEN [] ITALIË [] SPANJE [] JAPAN [] NOORWEGEN [] DENEMARKENII [] SLAVONISCH [] RUSLAND [] Portugees [] Canadees Frans [] Noords [] Turks [] Grieks West-Europees Latijn. CP858 [] CP860 [] WCP1252 [] CP860 [] WCP1252 [] CP857 [] [] WPC1250 [] WPC1253 [] GRIEKS [] [] WPC1255 [] Hebreeuws [] [] WPC1251 [] CP866 [] CP852 [] CP737 [] DOS Grieks [] [] CP858 [] CP864 [] Arabisch [] Farsi [] Iran [], CP936-GBK, Traditioneel Chinees, Vereenvoudigd Chinees	
Koppel	RS-232 [] serieel [] of USB Virtual COM	
Verbinding	Baud	Directe verbinding 9600 of 19200 bps
Betrouwbaarheid	MTBF	30000 uur
Kracht	Consumptie	5-24 VDC
Veiligheid	EMC-normen Veiligheidsnormen	FCC, CE, ROHS

