

Desktop 2D Mobile Barcode Scanner

(Model No.: OCBS-2103)

FEATURE:

- n Focus on the 1D/2D symbologies on the screen of mobile phone
- n Well designed on the light source to meet all kinds of high bright, low resolution mobile LED/LCD screen barcodes scanning

SPECIFICATION:

| Performance Characteristics | | |
|-----------------------------|--|---|
| Microprocessor | IOTC 0370 CHIP | |
| Resolution | 640×480 CMOS | |
| Interface | RS-232 (9.6~115.2Kbps), USB 1.1□HID-KBW□HID-POS□ | |
| Symbologies | 2D | PDF417□Data Matrix□QR code |
| | 1D | EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Coda bar, Code 128(Include FNC1 FNC2 FNC3 subset), Code 93, ITF-6, ITF-14□Interleaved 2 of 5,Industrial 2 of 5□Standard 2 of 5, Matrix 2 of 5□GS1 Data bar (RSS-Expand, RSS-Limited, RSS-14),Code 39(Include Code 39 FULL ASCII),Code 11,MSI-Plessey |
| Precision | ≥ 10 mil | |
| Light Source | White LED | |
| Scanning model | sense scanning, continuous scanning | |
| Precision | 10 mil | |
| Print Contrast Signal | ≥ 30% | |
| Filed angel | Diagonal□68°, Horizontal□42°, Vertical□54° | |
| Illumination | 0 ~ 100,000 LUX | |
| Power Consumption | 1 W | |
| Voltage | DC 5V, 0.5A□AC 100~240V, 50~60Hz | |
| Result feedback | Buzzer□Indicator light | |
| Dimension | 127.3mm(L) X 111.5mm (W) X 94mm(H) | |
| Weight | 300 g | |
| Environment | | |
| Operate Temperature | -10°C to + 50°C | |
| Storage Temperature | -20°C to + 60°C | |
| Humidity | 5% - 95%□non-condensing□ | |
| Programing Software | Quick Set, Programming Guide, uTools Lite | |
| Certification | FCC Part15 Class B, CE EMC Class B | |

