

China desktop handsfree USB bedrade 1d & 2d qr code omnidirectionele barcodescanner voor supermarkt

(M/N:OCBS-T215)

Functies:



Groot leesvenster;

Identificeer snel de 1D/2D-code van het scherm;

Verborgene anti-trek datakabel aansluiting.

Specificatie

Algemeen	
Model	OCBS-T215
Koppel	USB
Werkspanning	5V
Huidige starten	420mA
Werk huidige	400mA
Stand-bystroom	270mA
Prestatie	
Sensor	Totale belichting 640*480 CMOS-sensor
Lichtbron	Rode LED
Veldweergave	57,2° (H), 44,2° (V)
Bewegingstolerantie:	> 0.3m/s
Scanhoek	Pitch $\pm 70^\circ$ @ 0° Roll en 0° Skew Rol 360° @ 0° Pitch en 0° Skew Scheef $\pm 70^\circ$ @ 0° Roll en 0° Pitch
Symbolcontrast	20% minimaal reflecterend verschil
Immuniteit voor omgevingslicht	0-100.000 Lux
Typische scherptediepte	Code39 (5mil): 20 mm-80 mm, EAN13(13mil):10mm-160mm QR (15mil):10mm-140mm Gegevensmatrix (15 mil): 10 mm-100 mm PDF417 (10mil):10mm-120mm
Decodering vermogen:	(Codabar),(Code 39),(Code 32),(Industriële 2 van 5),(Interleaved 2 van 5),(Standaard 2 van 5),(Matrix 2 van 5),(Code 93),(Code 11),(Code 128),(UPC-A),(UPC-E),(EAN/JAN-8),(EAN/JAN-13),(GS1 DataBar(RSS14)(PDF417),(QR-code),(Micro QR),(Data Matrix),(Azteeks),(Hanxi-code)
Fysiek	
Gewicht	Bruto:640g
Pakket	230*170*95mm
Omgeving	
Werktemperatuur en vochtigheid:	0 tot 45 graden Celsius, 10% ~ 80% Geen condensatie
Opslagtemperatuur en vochtigheid:	-20 tot 60 graden Celsius, 10% ~ 90% Geen condensatie















Model: OCBS-T215

Interface: USB



OCBST2152214100001

Made in China





1. Introduction	1
2. Safety Precautions	2
3. Specifications	3
4. Operation	4
5. Troubleshooting	5
6. Appendix	6

1. Introduction

This power supply is designed to provide a stable and reliable power source for your equipment. It is designed to be used in conjunction with the power supply unit (PSU) and the power supply unit (PSU).

The power supply is designed to be used in conjunction with the power supply unit (PSU) and the power supply unit (PSU). It is designed to be used in conjunction with the power supply unit (PSU) and the power supply unit (PSU).

Special Precautions: This power supply has been tested and certified to meet the requirements of the power supply unit (PSU) and the power supply unit (PSU). It is designed to be used in conjunction with the power supply unit (PSU) and the power supply unit (PSU).

Copyright © 2000 by ocom. All rights reserved. This document is the property of ocom. It is not to be distributed, copied, or reproduced in any form without the written permission of ocom.

HOW TO USE THE POWER SUPPLY



1. Connect the power supply to the power supply unit (PSU) and the power supply unit (PSU). It is designed to be used in conjunction with the power supply unit (PSU) and the power supply unit (PSU).





2D Barcode Scanner
Model: OCBS-T215 Color: Black
Interface: USB CE FC
Power Input: 5V1A
OCBS T215 2214100001
Made in China