

433MHz draadloze 32bit laser barcodescanner met houder (Model: OCBS -W800)

SPECIFICATIES:

FYSISCHE KENMERKEN	
Lichtbron:	Zichtbare laserdiode (VLD) bij 650 nm
Scanner afmetingen :	168 mm * 72 mm * 93 mm (W * H * D)
Afmetingen ontvanger:	130 mm * 45 mm * 129 mm (W * H * D)
Materiaal:	ABS + TPR / aluminiumlegering
Gewicht:	370g
Scanning Mode:	Hand-held; Continue scanmodus.
Indicatielampje:	LED rood en blauw
Zoemer:	Zoemervolume instelbaar
PRESTATIEKENMERKEN	
Breedte van scanveld:	60 mm @ 30 mm (vanaf het motorvlak) 98 mm @ 100 mm (vanaf het motorvlak)
Diepte van het scanveld:	10 - 450 mm (contrast 0,9 densiteit 0,25)
Scan snelheid:	150 scans / sec
Scan precisie:	0.10-0.825mm
Bitfoutenpercentage:	1 / (5million)
Decodeervermogen:	UPC / EAN, UPC / EAN met supplementen, UCC / EAN128, Code39, Code 39 Volledige ASCII, Trioptische code 39, Code 128, Code 128 Volledige ASCII, Codabar, Interleaved 2 van 5, Discrete 2 van 5, Code 93, MSI, Code 11, RSS-varianten, Chinees 2 van 5, MSI / Plessey, VK / Plessey, UCC / EAN 128, Chinese code, GS1 DataBar (RSS) -serie
Accu:	3.7V / 750mAh Li-ion
Oplaadtijd:	3.0 uur
Scan tijd:	30 uur
Stroom:	95mA (werken); 25mA (standby)
Angles:	Spoed: 60 °; Tilt: 45 °
Werkende frequentie:	433MHz
Communicatie afstand:	200 m (open plaatsen)
Communicatie Interface:	USB
KARAKTERISTIEKEN VAN HET MILIEU	
Temperatuur:	-10 graden C to 45graad C (In gebruik), -40 graden C tot 60 graden C (opslag)
Relatieve vochtigheid:	5% -90% (niet-condenserend)
Drop Specification:	Bestand tegen herhaalde druppels van 1,5 m op het betonoppervlak
Omgevingsverlichting:	0 ~ 100.000 LUX
Elektrostatiche ontlading:	Voldoet aan ± 12KV luchtafvoer en ± 6KV aan contactontlading
Veiligheid certificaat:	CE, FCC, klasse 2, RoHS

Productdetails:



Wireless Barcode Scanner

OCBS-W800



Product Picture





Features

Simple but not easy

Integrated non-volatile memory



Data transmission distance reaches 200m in open area



Integrated non-volatile memory



Intelligent battery management system, real-time check the remaining battery



32bit decoder ensuring excellent decoding ability



All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
Memory	128K
Scanner Dimensions(W * H * D)	168mm * 72mm * 93mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	370g
Scanning Mode	Hand-held; Continuous Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	10-450mm (Contrast 0.9 Density 0.25)
Scan Speed	150 scans/sec

Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series
Battery	3.7V/750mAh, Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	95mA (working); 25mA(standby)
Angles	Pitch:60°; Tilt: 45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Communication Interface	USB
USER ENVIRONMENT CHARACTERISTICS	
Temperature	-10°C to 45°C (Operating), -40°C to 60°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.



Relevante documenten:

Wilt u meer informatie over producten weten?ormatie?alsjeblijft Klik hier.

- [Specificatie](#)
- [Gebruikershandleiding](#)