

# Ręczny laserowy skaner kodów kreskowych Auto Sense 1D ze statywem

(Model: OCBS -LA06)

## Specyfikacja:

| <b>Charakterystyka wydajności</b> |  |
|-----------------------------------|--|
| Źródło światła:                   | Widoczny laser (650-670nm)   |
| Częstotliwość skanowania:         | 100 skanów na sekundę  |
| Odległość odczytu                 | 2,5 ~ 600 mm (100% UPC / EAN)  |
| Typ skanera:                      | Dwukierunkowy  |
| Rozkład:                          | 0,10 mm (4 mil) w PCS 0,9  |
| Minimalny kontrast wydruku:       | 20%, minimalna różnica odbicia (@ 650nm)   |
| Zdolność dekodowania:             | UPC / EAN, UPC / EAN z dodatkami, UCC / EAN128, kod 39, kod 39 pełny ASCII, kod 39 triptyczny, kod 128, kod 128 pełny ASCII, codabar, przeplatany 2 z 5, dyskretny 2 z 5, kod 93, MSI , kod 11, ATA, warianty RSS, chiński 2 z 5 ... |
| <b>Charakterystyka fizyczna</b>   |  |
| Obsługiwane interfejsy:           | PS2, RS232, USB  |
| Napięcie:                         | DC + 5V +/- 5%   |
| Obecny:                           | 100 mA   |
| Prąd biegu jałowego:              | <40 mA   |
| Źródło prądu:                     | Zasilacz hosta lub zewnętrzny (RS232) zasilacz   |
| Kąt skanowania                    | Nachylenie 45 ° Elewacja 60 °  |
| Wymiary:                          | L165.42mm X W69.72mm X H89.67mm  |
| Waga:                             | 140g (bez podstawy)  |
| Stoisko                           | Z  |
| Kolor:                            | Kości słoniowej i czarny   |
| <b>Środowisko użytkownika</b>     |  |
| Temperatura robocza:              | 0 stopni C ~ 50 stopni C   |
| Temperatura przechowywania:       | -40 stopni C ~ 70 stopni C   |
| Wilgotność:                       | 5 ~ 95% wilgotności względnej, bez kondensacji   |
| Wyładowania elektrostatyczne:     | Potwierdź +/- 15KV wylot powietrza i +/- 8KV rozładowania kontaktowego   |
| Upuść specyfikacje:               | Odporny na wielokrotne upadki z wysokości 1,5 metra na beton   |
| <b>Bezpieczny:</b>                |  |
| EMI / RFI:                        | FCC klasy A i CE   |
| Bezpieczeństwo lasera:            | Laserowy produkt CDRH klasy 2  |

## Szczegóły Produktu:



*Handheld Laser  
Barcode Scanner*

**OCBS-LA06**

**Product Picture**





## Features

**Simple but not easy**

Auto-Induction built in, green design



High scan rate and long reading



distance



Excellent decode capability



KBW, RS232 and USB supported

Durable construction combined with future-proofing



## || All-round show





## Parameter

| Performance Characteristics |  |
|-----------------------------|--|
| Light Source:               | Visible laser (650-670nm)  |
| Scan Rate:                  | 100 scans per second   |
| Reading Distance            | 2.5 ~600mm (100% UPC/EAN)  |
| Scanner Type:               | Bi-directional   |
| Resolution:                 | 0.10mm (4mil) at PCS 0.9   |
| Print Contrast Minimum:     | 20%, minimum reflective difference (@650nm)  |
| Decode Capability:          | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5... |
| Physical Characteristics    |  |

|                          |  |
|--------------------------|--|
| Interfaces Supported:    | PS2, RS232, USB  |
| Voltage:                 | DC+5V+/-5%   |
| Current:                 | 100 mA   |
| Idle Current:            | <40 mA   |
| Power Source:            | Host power or external (RS232) power supply                      |
| Scanning Angle           | Inclination 45° Elevation 60°                                    |
| Dimensions:              | L165.42mm X W69.72mm X H89.67mm                                  |
| Weight:                  | 140g (without stand)   |
| Stand                    | With   |
| Color:                   | Ivory and black  |
| <b>User Environment</b>  |  |
| Operating Temperature:   | 0°C~50°C   |
| Storage Temperature:     | -40°C~ 70°C  |
| Humidity:                | 5~95% relative humidity, non-condensing                          |
| Electrostatic Discharge: | Confirm to +/-15KV air discharge and +/-8KV of contact discharge |
| Drop Specifications:     | Withstands multiple 1.5m drops to concrete                       |
| Safe:                    |  |
| EMI/RFI:                 | FCC Class A and CE   |
| Laser Safety:            | CDRH class 2 laser product                                       |

## Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C



## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com), Together we quest for the best.







Monica Fu



## OCOM Technologies Limited

---

**Add:** 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

**Tel:** 0086.755.8605.3207 ext 801

**Fax:** 0086.755.8605.3207 ext 868

**Web:** [www.ocominc.com](http://www.ocominc.com)

**E-mail:** [sales01@ocominc.com](mailto:sales01@ocominc.com), [sales01@ocomtech.com.cn](mailto:sales01@ocomtech.com.cn)

**Skype:** ocomsales01; **MSN:** ocomsales01@hotmail.com

**Ali TM:** cn1001868228; **QQ:** 1483705401

**Mobile/Wechat/Whatsapp:** 0086.189 4871 3992



Reliable One-Stop Supplier for POS and Auto-ID Related Products