

**Barcode Scanner poz Laser
(Model: OCBS-LA04)**

DANE TECHNICZNE:

Wydajność Charakterystyka	
Światło Źródło:	Widoczny laserowe (650-670nm)
Skanowanie Cena:	100 skanów na sekundę
Czytanie Dystans	2.5 ~ 600 mm (100% UPC / EAN)
Skanery Typ:	Dwukierunkowy
Rozdzielczość:	0,10 mm (4mil) w PCS 0,9
Druk Kontrast Minimalna:	20% minimalna różnica odbiaskowe (@ 650nm)
Rozszyfrować Zdolność:	UPC / EAN, UPC / EAN z supplementals, UCC / EAN128, kod 39, kod 39, kod ASCII pełnym 39 trioptic, kod 128, kod 128 full ASCII, Codabar, Interleaved 2 of 5, dyskretny 2 of 5, Code 93, MSI, Code 11, ATA, warianty RSS, chińskie 2 z 5 ...
Fizyczny Charakterystyka	
Interfejsy Obsługiwane:	PS2 RS232, USB
Napięcie:	DC + 5V +/- 5%
Prąd:	100 mA
Bezczynny Prąd:	& Lt; 40 mA
Moc Źródło:	Gospodarz zasilania lub zewnętrzne (RS232) Zasilanie
Skanowanie Kąt	45 ° nachylenia 60 ° Wysokość
Wymiary:	L165.42mm X W69.72mm X H89.67mm
Waga:	140g (bez podstawy)
Stać	Z
Kolor:	Kość słoniowa i czarny
Użytkownik Środowisko	
Operacyjny Temperatura:	0 °C ~ 50 °C
Magazynowanie Temperatura:	-40 °C ~ 70 °C
Wilgotność:	5 ~ 95% wilgotności względnej, bez kondensacji
Elektrostatyczny Absolutorium:	Potwierdź do +/- 15kV wpływ powietrza i +/- 8 kV wyładowania kontaktowego
Spadek Dane techniczne:	Wytrzymuje wielokrotnością 1,5 m upadki na beton
Bezpieczne:	
EMI / RFI:	FCC i CE klasy
Bezpieczeństwo lasera:	Laser klasy 2 CDRH produkt

Szczegóły Produktu:



*Handheld Laser
Barcode Scanner*

OCBS-LA04



Product Picture





Features

Simple but not easy

Auto-Induction built in,
green design



High scan rate and long reading



High scan rate and long reading distance



Excellent decode capability



KBW, RS232 and USB supported



CDurable construction combined with future-proofing



||| All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Physical Characteristics	
Interface Supported:	PS2, RS232, USB

Interfaces supported:	RS232, RS485, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0°C~50°C
Storage Temperature:	-40°C~70°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union

- 7. Escrow
- 8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.





Odpowiednie dokumenty:

Chcesz wiedzieć więcej inf produktówReformacji?Proszę Kliknij tutaj. 

[Specyfikacja](#)

[Instrukcja obsługi](#)