

15 inch all in one colorful touch pos system

(M/N:POS8829)

## Feature:

- 1.Good-looking design is suitable for many POS field
- 2.Low power-consumption solution guarantees its stable quality and safety
- 3.LED/LCD customer display optional
- 4.MSR optional
- 5.Wifi optional

## Application:

- 1.Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- 2.Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- 3.Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- 4.Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

## Specifications:

|                           |  |
|---------------------------|--|
| Model                     | POS8829  |
| Optional Color            | Black/ Wine red  |
| Optional Peripherals      | ISO Track1/2/3 Magnetic Stripe Reader; LCD Customer display; LED8; WIFI  |
| Main Board                | Intel Chipset  |
| CPU                       | 1037U dual core 1.8G   |
| Chipset                   | 1037U + ICH8 Chipset   |
| Memory Support            | DDRIII 1066/1333*1 2GB(up to 4GB)  |
| Hard Driver               | SSD32GB  |
| LCD panel Size            | 15 inch TFT LCD  |
| Brightness                | 350cd/m <sup>2</sup>   |
| Resolution                | 1024*768(max)  |
| Touch Screen              | 5 wire resistive touch screen  |
| View Angle                | Horizon: 150; Vertical: 140  |
| I/O port                  | 1* power button<br>PS2 mouse*1; PS2 keyboard*1<br>Serial*3 DB9 male<br>Parallel * 1, DB25 Parallel port<br>VGA(15Pin D-sub)*1<br>LAN: RJ-45*1    HDMI * 1<br>USB(2.0) * 6<br>Audio out*12*Internal Speaker(option), MIC IN*1 |
| Operating temperature     | 0 to 40 degree centigrade  |
| Storage temperature       | -20 to 60 degree centigrade  |
| Power Consumption         | 35W(max)   |
| Compliance                | FCC Class A/CE Mark/LVD/CCC  |
| Packing dimension/ Weight | 440*270*425mm / 8 KGS  |

|                  |  |
|------------------|--|
| Operating System | Windows XP Professional Embedded (WEPOS, Linux compatible) |
| Power adapter    | 110-240V/50-60HZ AC power Input,                           |