

19-inch Touch Screen LCD Display

(Model No: TM1901)

Features:



Multifunctional setting key;

5 or 4 wire touch panel for option;

Grade A LCD panel with LED backlight;

High resolution 1280*1024@60HZ;

Suitable for all kinds of high-intensity working environment.

Specification

Model	TM-1901
Name	19 inch touch screen display
Color	Whole black color machine usually
Material	Metal base with plastic body
VESA	75*75mm for wall mounting(need extral wall mounting bracket)

OSD Language	Support 8kinds of international languages
Display	
Display area	376.32(W)×301.056(H) mm
Pixel pitch	0.294*0.294
Aspect ratio	4:3
Resoluiton	1280*1024
Brightness	300cd/m2
Contrast	1000:1
Display color	16.7M
View angle	Horizon: 170; Vertical :160
Response time	5ms
Touch function	
Touch screen	5-wire resistive touch panel,4-wiretouch screen for option
Structure	ITO Film and ITO Glass FIT
surface treatment	Fog surface, anti-glare
Responding speed	<5ms
Surface hardness	Pencil hardness:3H
Total light transmittance	Up to 85%
Touch life	>35000000 times
Connectivity	
Rear I/O	12V DC in jack*1
	USB *1 for touch function
	15PIN D-sub VGA *1
	HDMI*1 for option
	Audio in*1 for option (built in speaker for option)
Side key function	Auto, Menu,Up,Down,Power Swicth
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Package	
Package with foam inside	570*130*500mm/7.5kg
5 in 1 carton	570*490*500mm/28kg
Accessories	
Power adapter	110-240V/50-60HZ AC power input ,DC12V/4A output adaptor
Cable	Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option)
Touch related	Touch pen,driver disk
Other	
Certification	CE,ROHS,CCC,FCC













