

2 Inch Adhesive Paper Printing Direct Thermal Label Printer

(M/N:OCBP-006)

- 1.Support thermal roll paper / adhesive paper
- 2.The print head with adjustable pressure
- 3.Automatic paper checking function
- 4.Temperature adaptive control
- 5.Modular design, to meet different application requirements

Printing method	Direct thermal
Resolution	203DPI
Print width	20-60mm
Printing speed	MAX:127mm/s[MIN:50.8mm/s]
Memory	DRAM: 4M FLASH: 4M
Print head temperature	Thermistor
Paper exists detection	The micro switch
Interface	USB
Paper presence detection	Paper presence detection
Barcode	CODE128[EAN128]ITF[CODE39]CODE93[EAN13][EAN13+2][EAN13+5][EAN8][EAN8+2][EAN8+5][CODABAR][POSTNET][UPC-A][UPCA+2][UPCA+5][UPC-E][UPCE+2][UPC-E+5][CPOST][MSI][MSIC][PLESSEY][ITF14][EAN14] Qrcode[DM Code] PDF417
Internal font	FONT 0 to FONT 8
Enlargement & rotation	[0][90][270][360] 1 to 10 times enlargement in both direction; 0*[90][270][360] rotation
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM
Paper type	Paper roll, sticker, adhesive sticker, etc
Paper width	20mm[60mm]
Roll external	MAX 80mm
Roll inner diameter	MIN 25mm
Paper off type	Tear off
Power supply input	DC12V, 3A
Weight	1.04KG
Dimensions	190(D) x 135(W) x 137(H)mm
Work environment	5[45°C, 20[80%RH(no condensation)
Storage environment	[40][55°C][≤93%RH][40°C]









OCBP-006





OCBP-006

