

58mm thermal receipt printer OCPP-587-R RS232/COM/Serial Port

(M/N:OCPP-587-R)

Product description:

OCPP-587 is a Mini 58MM thermal printer, the design exquisite fashion, small and smart, with highly technological sense. Using large motor and a big gear movement design, drag 83MM large diameter roll and achieve 130 mm / s high speed printing at the same time, the perfect solution to solve the problem of common 58mm printer support small diameter roll, print speed slow, enable print more efficient. At the same time, provides a rich interface, including network port (100M), WIFI, Bluetooth, GPRS, enable print more flexible and convenient.

Product performance:

- Appearance compact design, fashion technology;
- Easy paper feed structure, simple and convenient operation;
- High reliability of large motor and large gear movement;
- 130 mm / s speed print, significantly improve the printing efficiency;
- Big paper warehouse design, the perfect support for 83MM large diameter rolls;
- Rich interface optional: USB, COM, Internet (100M), WIFI, Bluetooth, GPRS;
- Support GB18030 large font and multi language ;
- Supports LOGO and graphics downloads and print;
- Supports Windows, Linux, Android and IOS system print;
- 100M Ethernet interface, print quickly while avoiding losing bills.

Printer Parameters:

Items	Parameters	
Print parameters	Printing Method	Thermal Line
	Printing Method	48MM
	Resolution	384dots/Line[8dots/mm][203dpi]
	Printing Speed	130mm/Second
	Interface Type	USB[COM]Internet[100M]WiFi[GPRS]Bluetooth
	Line Spacing	3.75 mm[can adjust line spacing by command]
	Line No.	Font A:32 character/Line Font B:42 character/Line
	Character	Simple,traditional Chinese:16 lines Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANKcharacter[Font A][1.5x3.0mm][12x24]
	Bar code Character	Extended character set
Bar code		1D bar code[UPC-A][UPC-E][EAN13][EAN13]JAN8[EAN8][CODE39][ITF/CODABAR][CODE39][CODE128 2D bar code][QRCODE
Graphics printing	Graphics printing Supports bitmap download and print	
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	±83mm
Print commands	Feed Method	Easy feed[Clamshell feed]
	Commands	ESC/POS
Power	Power Adaptor	Input:AC 100V-240V,50-60Hz Output:DC 12V/1A
	Buffer	Casher Drawer output Input Buffer NV Flash
physical characteristics	Weight	750g
	Dimension	160*115*127(MM)
Environment	Working	Temp[5 ~ 45°C] Humidity[10 ~ 80%
	Storage	Temp[-10 ~ 50°C] Humidity[10 ~ 90%][No dew]
Reliability parameter	Print Head Life	1000M[print density≤12.5]
	Software	Driver Android,IOS,Linux,_WinXP,Win7,Win8,Win8.1,Win10



0CPP-587





0CPP-587



www.ocominc.com



Thans & Best Regard
Harold Hu

OCOM Technologies Limited
Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District,
Shenzhen 518054, China;
Website: www.ocominc.com, www.possolution.com.cn ;
E-mail: sales14@ocominc.com ;
Skype: [sales14@ocominc.com](https://www.skype.com/user/sales14@ocominc.com)
MSN: ocomsales14@hotmail.com ;
Whatsapp: 0086.18948789890;
Wechat: 0086.18948789890;
Mobile: 0086.18948789890;

QQ: 1467261417;

Tel: 0086.755.86053207-814;

Fax: 0086.755.86053207-868;