

58mm thermal receipt printer with built-in power adaptor ocpp-58E-W WIFI Port (OCP-58E-U-W)

Product Introduction:

OCP-58E is a well-designed economic printer for common thermal bill printing, this mold is with solid material, Exquisite workmanship. Transparent cover design, simple and fashion, easy for users to know the paper rolls' Using status, OCP-58E adopt built-in power supply, not only can save space, but also easy for users to configure and use the printers. It's a very good choice for economical printing.

Product Features

- Simple and fashion, With solid material, exquisite workmanship.
- Easy paper install structure, simple and convenient to operate
- Built-in power supply design, to save space and more convenient to configure;
- Transparent cover design, the user can know the paper roll's using status anytime;
- Support GB18030 big font, easy to print uncommon characters
- Support multi language print, suitable for users all over the world;
- Support download and print LOGO & graphics ;
- Support Windows, Linux, Android and IOS system printing

Application Area

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters

Items	Parameters	
Print parameters	Printing Method	Thermal Line
	Printing Width	48MM
	Resolution	384dots/Line(8dots/mm)(203dpi)
	Printing Speed	90mm/Second
	Interface Type	USB/USB + Bluetooth
Character	Line Spacing	3.75 mm(Can adjust line spacing by command)
	Line No.	Font A:32 character/Line Font B:42 character/Line
	Character	Simple, traditional Chinese-16 lines Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANKcharacter[Font A](1.5×3.0mm)(12×24dots) Font B(1.1×2.1mm)(9×17dots) Simplified/Traditional Chinese(3.0×3.0mm)(24×24 dots)
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC858/Iran/Latvian/Arabic/PT151.1251/PC737/WPC1257/Thai/Vietnam/PC864/PC1001/Latvian/(PC1001)/(PT151.1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Graphics printing	Bar code	UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/CODABAR/CODE93/CODE128
	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
Print commands	Diameter	≤60mm
	Feed Method	Easy feed(Clamshell feed)
Power	Commands	ESC/POS
	Power Adaptor	Input[AC 100V-240V 50-60Hz Output[DC 12V/2A
Buffer	Casher Drawer output	DC 12V/1A
	Input Buffer	4K
physical characteristics	NV Flash	40K
	Weight	590g
Environment	Dimension	185*130*112(MM)
	Working	Temp[5 ~ 45°C] Humidity[10 ~ 80%
Reliability parameter	Storage	Temp[-10 ~ 50°C] Humidity[10 ~ 90%(No dew)]
	Print Head Life	50KM(print density 12.5)

Contact: Harold Hu

OCOM Technologies Limited
Website: www.ocominc.com;
E-mail: sales14@ocominc.com ;
Skype: [sales14@ocominc.com](https://www.skype.com/people/sales14@ocominc.com)
MSN: ocomsales14@hotmail.com ;
Whatsapp: 86.18948789890;
Wechat: 18948789890(ocomsales14);
Mobile: 86.18948789890;
QQ: 1467261417.