

80 mm MiniPortable Thermal Reception Printer (M/N: ocpp-M085)



ProductsCharacteristics

- Business style design,More fashion
- 1. d support, 2. D barcodePrinting
- While being compatible withWindows, Linux, Android and iOS systems
- with rechargeable 2500mahLithium polymer battery, super battery life, with intelligent power Economy and PowerConsumption control functions to ensure a longer printing time
- USB support, com, Bluetooth, WiFi ,USB + Bluetooth (v2.0), USB + bluetooth (v3.0 + v4.0)
- Special power remainingLight, to control the power of the printer at any time
- Sound and light supportReminder when the lack of paper or abnormal printing
- Anti drop of 1.5 m of cementFloor

Application:

Storage, transportation,Logistics, supermarket, tobacco, hydropower, mobile government affairs, mobilePolice, posts and other industries

Settings

Point	Parameter
Print setting	Printing Method
	Thermal Online
	Effective print width
	72
	Resolution
	576 Points/Line8dots/mm203
	Priting Speed
	90 mm/s
Bar code character	Interface
	USB (Standard USB 2.0 communication protocol, (Windows support, Linux, Android, iOS) Bluetooth (Bluetooth 2.0, Bluetooth 3.0 + 4.0, support Android, iOS) WiFi (2.4 GHz, ATA, AP, ATA + AP Mode)
	Online Spacing
	3.75 mmCan Adjust line spacing by order
	Line No.
	Font A:48 character/ Character/Line of characters b:64 Single, Traditional Chinese-24 lines
	Character
	The standard GB18030 simplified/Traditional Chinese Character Library
Graphic printing	Character of SCNPolice has
	1.5 × 3.0 mm12 × 24 points
	Police b1.1 × 2.1 mm9 × 17 points Simplified/Traditional3.0 × 3.0 mm (24 × 24dots)
Energy Saving Mode	Extended Character Set
	pc437/Katakana/PC850/PC860/pc863/PC865/Westeurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/East/PC858/IranII/Latvian/Arabic/PT151, 1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151, 1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar Code
Indicator	1 D BarcodeUPC-A/UPC-E/Jan13 (EAN13)/JAN8 (EAN8) Code39/ITF/ Codabar/code93/code128
	2d. Bar codeQRCode
	Supports download and bitmap printing
Dection	Graphics Printing
	Smart Energy saving
	Support
Paper	Variable Speed printing
	Support
	Consumption
Print commands	Dormancy
	Support
	Sensor
Power	Lack of paper detection
	Power Display
	Support
Buffer	Load Indicator
	Support
	Lack of paper
Physical characteristics	Support
	Beep
	Lack of paper, abnormal alarm printing
Type	Type
	Thermal
	Width
Capacity	79.5 mm
	Thickness
	≤ 0.12 mm
Charger	Diameter
	≤ 40 mm
	Feed
Entry	EasyClamshell Feed
	Commands
	ESC/POS
Nv Flash	Type
	Rechargeable Lithium Polymer Battery
	Capacity
Weight	2500mah/7 .4v, can be charged more than 800 times
	Durable printing 150 meters or 4 hours under normal use
	Charger
Dimension	9.0 V/2 A
	Entry
	4
Weight	Nv Flash
	kb
	Weight
Dimension	G
	Dimension
	114 * 103 * 50 (mm)

Environment	Of	Temp□5 ~ 45□ Moisture□10 ~ 80%
	Storage	Temp□-10 ~ 50 □Moisture□10 ~ 90%□No Dew□
Reliability	Print The life of the head	50□Printing Density ≤ 12.5□
Software	Pilot	Android, iOS, Linux, WinXP, Win7, Win8, Win 8.1, Win10