

# 80mm POS receipt thermal printer with auto cutter

(Model No.: OCPP-80Y)

## Keywords :

80mm thermal printer,80mm receipt thermal printer,80mm pos printer

## Features:

1. Desktop or wall-mounted type for option.
- 2.Supports multi 1D barcodes
- 3.160mm/s printing speed
- 4.Supports 256KB NV Logo storage and 2M big buffer memory.

## Technical parameters

Printing method:	Direct thermal
Printing speed:	160mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line512 Dots/line
Line's pacing :	3.75mm□Adjustable by commands□
Print command:	Compatible with the ESC/POS command
Interface type:	USB
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V□50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0□45) humidity(10□80%)□Non- condense□
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10□60°C); Humidity(10□90%)
Character size:	ANK□FontA:1.5*3.0mm/ FontB□1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA□EAN13□JAN8□EAN8/CODE39/ITF /CODE93/CODE128
Characters:	PC347□Standard Europe□□Katakana□PC850□Multilingual□□PC860 □Portuguese□□PC863□Canadian-French□□PC865□Nordic□□West Europe□ Greek□Hebrew□East Europe□Iran□WPC1252□PC866 □Cyrillic#2□□PC852□Latin2□□ PC858□IranII□Latvian□Arabic□PT151□1251□

Physical characteristics	Weight: 1.25Kg
--------------------------	----------------