

80mm Thermal POS Ticket printer With automatic cutter (OCPP-80N)

Features:

- QR code printing support
- Serial Port + USB + LAN Interface
- effective 100MB Ethernet interface to transfer data
- Support for International Languages
- Support rewrite function
- Printer Status Monitor
- Built-in Web page, set the printer directly
- Supports 2048K bytesInput Buffer

Specification:

Printing Methods	Direct Thermal
Print width	76 mm
Column capacity	576 dots / line 512 dot / line
Print speed	300 mm / sec
Interface	Serial Port + USB + Lan
Paper	79.5 ± 0.5 mm × φ80mm
Line spacing	3.75 mm (adjustable by the command)
Column No.	80 mm paper: Font A - 42 columns, or 48 / Font B - 56 or 64 /
Character Size	ANK,Font A:1.5 × 3.0 mm(12 × 24 points) Font B:1.1 × 2.1 mm(9 × 17 □) Chinese, Chinese Traditional: 3.0 × 3.0 mm(24 × 24 points)
Cutter	
Automatic cutter	All or part (optional)
Bar code character	
Expand	PC347(European standards).Katakana,
Character	PC850(multilingual).PC860(Portuguese).
sheet	PC863(Canada, France).PC865(Nordic).
	Western Europe,Greek,Hebrew,Eastern Europe,Iran,WPC1252,PC866(Cyril # 2). PC852(Latin 2).PC858,IranII,Latvia,Arabic,PT151(1251)
Barcode types	UPC-A / UPC-E / JAN13(EAN13)/ JAN8(EAN8)/ CODE39 / ITF / CODABAR / CODE93 / CODE128
QR code	QR code
Buffer	
Input buffer	2048K bytes
NV Flash	256K bytes
Power	
Power Adapter	enter:AC 110V / 220V, 50~60 Hz
Power source	Export:DC 24V / 2.5A
Cashbox	DC 25V / 1A
Yield	
Physical Characteristics	
weight	1.48KG
size	185 × 140 × 134 mm (D × W × H)
Environmental requirements	
working environment	Temperature (0~45) and humidity (10~80%)
Memory surroundings	Temperature (-10~60 °C), humidity (10~80%)
Reliability	
Tool life	1 million cuts
Print head life	100KM

1. 3 inches thermal printer Interface:

Serial Port + USB + Ethernet port

2. Receipt Printer Optional power adapter:

Relevant documents:

[Driver and CD files](#)