

## 80MM thermal printer with auto cutter

(Model: OCPP -80Y)



### Feature:

Desktop or wall-mounted options.

Support multiple barcode printing

USB, USB + LAN, USB + RS232, optional URL

Support 256KB NV logo storage and 2M large buffer memory.

Small package, save transportation cost

### Technical parameter:

|                    |  |
|--------------------|--|
| Printing method:   | Direct heating                                 |
| Printing speed:    | 160 mm/sec                                     |
| Roll width:        | 79.5±0.5mm                                     |
| Printing diameter: | Φ80mm  |
| Paper thickness:   | 0.06-0.08mm                                    |
| Column capacity:   | 576 dots/line512 dots/line                     |
| Line spacing :     | 3.75mm (adjustable by command)                 |
| Print command:     | Compatible with ESC / POS commands             |
| Interface Type:    | USB, USB + LAN, USB + RS232, USB + RS232 + LAN |
| Tool life:         | Cut 1 million                                  |
| Print head life:   | 100 km   |
| Input buffer:      | 2048Kbytes                                     |
| NV Flash:          | 256K bytes                                     |
| Power Adapter:     | AC110V / 240V, 50~60HZ                         |
| power supply:      | DC 24V / 2.5A                                  |

|                           |   |
|---------------------------|---|
| Cash drawer supply:       | DC 24V / 1A   |
| working environment:      | Temperature (0~45) Humidity (10~80%) (non-condensing)   |
| working environment:      | Temperature (0-45) degrees Celsius, humidity (10-80%) non-condensing  |
| Storage environment:      | Temperature (-10~60°C); Humidity (10~90%)   |
| Character size:           | ANK, FontA: 1.5 * 3.0mm / FontB: 1.1 * 2.1mm  |
| Barcode:                  | UPC-A / UPC-E / JA (EAN13) / JAN8 (EAN8 / CODE39 / ITF / CODE93 / CODE128, (QR code and PDF 417 optional)   |
| Features:                 | PC347 (Standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canada-France), PC865 (Northern Europe), Western Europe, Greece, Hebrew, Eastern Europe, Iran, WPC1252, PC866 (Siri Irvine #2), PC852 (Latin 2), PC858, IranII, Latvian, Arabic, PT151 (1251) |
| Physical characteristics: | Weight: 1.25Kg  |





# OCPP-80Y





# OCPP-80Y





# OCPP-80Y







Optional power adapter:



Application areas:



## ▶ Application scenario

Logistics



Warehouse management



Supermarket



Clothing label



Jewelry label



Restaurant



### Related Products:

[Unique 80mm high speed POS thermal printer](#)