China Factory Supplier USB and Wireless Laser Barcode Scanner

Features:

China Factory Supplier USB and Wireless Laser Barcode Scanner

2.4 G wireless laser barcode scanner;

Scan Speed:100scans/sec;

Data transmission distance reaches 30m in open area;

Scan Time: 30hours;

SPECIFICATION:

PHYSICAL CHARACTERSTICS	
Light Source:	Visible Laser Diode (VLD) @ 650 nm-670nm
Scanner Dimensions:	164mm * 67mm * 95mm(W * H * D)
Receiver Dimensions:	130mm*45mm*129mm(W * H * D)
Material:	ABS+TPR /Aluminium alloy
Weight:	235g
Scanning Mode:	Hand-held; bidirectional Scanning Mode.
Indicator Light:	LED Red and Blue
Buzzer:	Buzzer Volume Adjustable
PERFORMANCE CHARACTERSTICS	
Width of Scan Field:	60mm@30mm[From engine face[]
	98mm@100mm[from engine face[]
Depth of Scan Field:	2.5-600mm Contrast 0.9 Density 0.25
Scan Speed:	100 scans/sec
Scan Precision:	0.10mm[]4mil[] PCS0.9
Bit Error Rate:	1/(5million)
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39,
	Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full
	ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI,
	Code 11, RSS variants, Chinese 2 of 5
Battery:	3.7V/750mAh,Li-ion
Charge Time:	3.0 Hours
Scan Time:	30 Hours
Current:	100mA (working); 40mA(standby)
Angles:	Pitch:60°; Tilt: 45°
Communication	
Distance:	30m
Working Frequency:	2.4G
Communication	
Interface:	USB
USER ENVIRONMENT CHARACTERSTICS	

	Odegree C to 50degree C (Operating), -40degree Cto 70 degree
Temperature:	C (Storage)
Relative Humidity:	5%-90%(Non-Condensing)
Drop Specification:	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination:	0~100,000 LUX
Electrostatic Discharge:	Conforms to ± 12 KV air discharge and ± 6 KV of contact discharge
Safety Certificate:	CE, FCC, Class 2, RoHS

Products Details:

 $\mathbf{x} \mathbf{x} \mathbf{x} \mathbf{x}$

Relevant documents:

Do you want to know more product information?Please Click here.

▼

Specification