

China barcode scanner machine factory (Model: OCBS-W600)

SPECIFICATION:

PHYSICAL CHARACTERISTICS	
Light Source:	Visible Laser Diode (VLD) @ 650 nm-670nm
Scanner Dimensions:	164mm * 67mm * 95mm(W * H * D)
Receiver Dimensions:	130mm*45mm*129mm(W * H * D)
Material:	ABS+TPR /Aluminium alloy
Weight:	235g
Scanning Mode:	Hand-held; bidirectional Scanning Mode.
Indicator Light:	LED Red and Blue
Buzzer:	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field:	60mm@30mm□From engine face□ 98mm@100mm□from engine face□
Depth of Scan Field:	2.5-600mm□Contrast 0.9 Density 0.25□
Scan Speed:	100 scans/sec
Scan Precision:	0.10mm□4mil□ PCS0.9
Bit Error Rate:	1/(5million)
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5
Battery:	3.7V/750mAh,Li-ion
Charge Time:	3.0 Hours
Scan Time:	30 Hours
Current:	100mA (working); 40mA(standby)
Angles:	Pitch:60°; Tilt: 45°
Communication Distance:	30m
Working Frequency:	2.4G
Communication Interface:	USB
USER ENVIRONMENT CHARACTERISTICS	
Temperature:	0degree C to 50degree C (Operating), -40degree Cto 70 degree C (Storage)
Relative Humidity:	5%-90%(Non-Condensing)
Drop Specification:	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination:	0~100,000 LUX
Electrostatic Discharge:	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate:	CE, FCC, Class 2, RoHS

Product Details:

