

# 20X2 Characters Double Line LCD Customer Display

(ModelNo.: LCD220C)

## Features:

Supports 11 command modes included EPSON etc.;

Compatible with 95 national languages;

Power supply from 5V to 24V to prevent any mindless use of improper power input;

Can show 2 lines \* 20 columns;

OPOS/JPOS driver is standard.



## Data sheet:

General	Display method	TN-LCD negative display (White on the Blue background)
	characters	20 columns*2 lines
	brightness	1200cd/m2
	Character font	16*16 dot matrix
	Character type	95 Alphanumeric[]32 international characters
	Character Size	9.92[H]x7.135[W]mm
	Dot size[XxY]	0.426(H) x 0.6(V)mm
	Window size	142.7(H) x 19.82(V)mm
	PCB Size	160[L]x36.6[W]x10.1[H]mm
	Weight	Approx.65.5 grams
Commands Mode	LD220[]EPSON POS D101[]AEDEX[]UTC/S[]UTC/P[]ADM788[]DSP800[]CD5220[]EMAX[]LOGIC CONTROL	
Language Support	FRANCE[]GERMANY[]U.K[]DENMARKI[]SWENEN[]ITALY[]SPAIN[]JAPAN[]NORWAY[]DENMARKII[]SLAVONIC[]RUSSIA[]Portuguese[]Canadian French[]Nordic[]Turkish[]Greek West European Latin.CP858[]CP860[]WCP1252[]CP857[]TURKISH[]Polish[]WPC1250[]WPC1253[]GREEK[]WPC1255[]Hebrew[]WPC1251[]CP866[]CP852[]CP737[]DOS greek[]CP858[]CP864[]Arabic[]Farsi[]Iran[],CP936-GBK,	
Interface	RS-232[]serial[]or USB Virtual COM	
Connection	Baud	Direct connection 9600 or 19200 bps
Reliability	MTBF	30000 hours
Power	Consumption	5-24 VDC
Safety	EMC standards Safety standards	FCC[]CE[]ROHS

Words:POS Customer Display,LCD POS Customer Display,China Display Factory