

## **58mm Thermal Printer With Built-in Power Supply**

(OCP-58X)



### **Product Introduction:**

OCP-58X is a well-designed economic printer for common thermal bill printing , It is adopt built-in power supply,not only can save space,but also easy for users to configure and use the printers.It's a very good choice for economical printing.

### **Product Features**

Simple and fashion,With solid material,exquisite workmanship.

Easy paper install structure,simple and convenient to operate

Built-in power supply design, to save space and more convenient to configure;

Support multi language print, suitable for users all over the world;

Support download and print LOGO&graphics ;

### **Application Area**

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

## Parameters

Items	Parameters	
Print parameters	Printing Method	Thermal Line
	Printing Width	48MM
	Resolution	384dots/Line□8dots/mm□203dpi□
	Printing Speed	90mm/Second
	Interface Type	USB□Parallel
	Line Spacing	3.75 mm□Can adjust line spacing by command□
	Line No.	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
	Character	Standard GB2312 simplified Chinese Fonts
	Character Size	ANKcharacter□Font A□1.5×3.0mm□12×24dots□ Font B□1.1×2.1mm□9×17dots□ Simplified/Traditional Chinese□3.0×3.0mm(24×24 dots□
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed Method	Easy feed(Clamshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input□AC 100V-240V,50-60Hz Output□DC 12V/2.6A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	32 KB
	NV Flash	64 KB



Selftest  
Version : 1.9F  
Speed : 90mm/s  
Interface : Parallel  
Default code page: Page0  
Print Density : Light  
Chinese character: Yes  
Image NV Download: Yes  
Modify date : 2013/12/30  
Resident Character:  
Alpha-numeric



# OCPP-58X





OCPP-58X





**Power plug for option:**



**Application Area:**

## ▶ Application scenario

Logistics



Warehouse management



Supermarket



Clothing label



Jewelry label



Restaurant

