

Model	POS-M1106-W	POS-M1106-A
Name	11.6 inch all in one Windows touch screen pos terminal	11.6 inch all in one Android touch screen pos terminal
Housing	plastic with metal combined	
Color	Whole gray color	
Main screen size	11.6 inch touch screen monitor	11.6 inch touch screen monitor
Resolution	1366*768,1920*1080 for option	1366*768,1920*1080 for option
Brightness	2 300cd/m	
View angle	Horizon: 160; Vertical :150	
Touch screen	multi-point projected G+G capacitive touch	
<b>Performance</b>		
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz	RK 3568,Cortex-55,quad core 2.0GHz /RK 3288 quad core 1.8GHz CPU for option
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB (default) 2GB/8GB for option	On board 2GB DDRIII
Storage device	Msata SSD 64GB or higer, up to 256GB	32GB eMMC, support 32GB TF card expanded for option
Audio	On board Real Tek ALC662 audio chip	On board Real Tek audio chip ALC5640
LAN	10/100 Mbs, Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10M/100M RTL8201F,10M/100M/1000M RTL8211E for option
Operating System	Windows 7/8/10, Embedded,WEPOS,Linux	Android 11
<b>Connectivity</b>		
External port(J1900/RK3288) I/O	power button*1	
	12V DC in jack*1	
	COM(RS232) * 1, up to 3ports	
	LAN:RJ-45*1	
	RJ11 for Cash drawer *1 for option	RJ11 for Cash drawer *2 for option
	VGA(15Pin D-sub)*1	TF card slot*1
	USB *5	USB *5
	MIC in*1 Audio out*1	N/A
<b>Options</b>		
80mm thermal printer	direct thermal printing	
	170mm/s printing speed	
	79.5-/+ 0.5mm paper width and printable width 72mm with auto cutter function and thermal head life 100km	
58mm thermal printer	direct thermal printing	
	70mm/s printing speed	
	57.5-/+ 0.5mm paper width and printable width 48mm thermal head life 50km	
MSR	ISO7811 1/2/3 Tracks, Support Dual-swiping	

NFC	ISO14443TypeA (function for not installing 5.0 inch display)
scanner	1D/2D barcode (function for not installing 5.0 inch display)
Customer display	2*20 VFD or 2*20 LCD ( function for not installing 5.0 inch display)
nd 2 display	5.0 inch 800*600 resolution non-touch display
Battery	5200mAh large capacity battery
<b>Package</b>	
Weight	Net 2.4Kg Gross 3.1Kg
Package with foam inside	400*390*190mm
<b>Environment</b>	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
<b>Accessories</b>	
Power adapter	110-240V/50-60HZ AC powerinput ,DC12/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
CD driver	Motherboard driver and touch driver inside
<b>Other</b>	
Compliance	FCC Class A/CE Mark/LVD/CCC