

High quality 10" electronic cash register machine with embedded printer

(M/N:POS-B10/B10-A)

Features:

Intel Celeron Processor J1900 Quad core 2.0GHz High Configuration CPU for Windows system
2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system
2GB RAM+8GB ROM standard (Android)
2GB RAM+32GB SSD standard (Windows)
Multi-point capacitive touch screen
Embedded 58mm or 80mm thermal printer(Optional)
Embedded MSR RFID reader(Optional)
Stylish display pane

Applications:

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Pictureshow:



Parameter:

| | |
|----------------|--|
| Model | POS-B10/POS-B10-A |
| Main Board① | Intel CeleronProcessor J1900 Quad core 2.0GHz (Windows) |
| Main Board② | 2.0GHz A83T ARM 8-Core Cortex-A7 Processor (Android) |
| OS① | Windows7(Beta) |
| OS② | Android 5.1 |
| Memory① | 2GB RAM 32GB SSD (Windows) |
| Memory② | 2GB RAM 8GB ROM (Android) |
| Touch Screen | Multi-point capacitive touch |
| Screen Size | Main screen10.1 inch,Vice screen10.1inch |
| Color | Black or Wihte |
| Printer | 58mm big gear thermal printer or 80mm thermal printer with Auto cutter(Optional) |
| I/O port①J1900 | USB*4 |
| | RJ45*1 |
| | RJ11*1 |
| | HDMI*1(for vice screen) |
| | DB9 RS232 port *1 |

| | |
|---------------------------|---|
| I/O port(@A83T) | RJ11*1 |
| | TF slot *1 |
| | RJ45*1 |
| | HDMI*1(for vice screen) |
| | USB*2 |
| | DB9 RS232 port*1 |
| | Audio*1 |
| | USB OTG port |
| Operating temperature | 0°C to 40°C |
| Othter Function (Andriod) | Bluetooth, WIFI,GPS |
| Optional items(Windows) | LCD VFD display,RFID,MSR camera,3G, DB25 parallel port, DB9 RS232 port*3 Other size Screen |
| Optional items(Andriod) | 3G,camera, LCD VFD display,RFID,MSR,Other size Screen |
| Storage temperature | -20°C to 60°C |
| Packing dimension | 46*43*51cm |
| Power adapter | 110-240V/50-60HZ AC power, Input DC12/5A out put |