

80mm thermal pos printer with Auto Cutter

Printing method:	Direct thermal
Printing speed:	230mm/s □ 260mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line □ 512 Dots/line
Line's pacing :	3.75mm □ Adjustable by commands □
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+Lan/36P parallel port/25P serial +USB/LAN
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V □ 50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0 □ 45) humidity(10 □ 80%) □ Non- condense □
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10 □ 60°C); Humidity(10 □ 90%)
Character size:	ANK □ FontA:1.5*3.0mm/ FontB □ 1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA □ EAN13 □ JAN8 □ EAN8/CODE39/ITF /CODE93/CODE128 QRCode
Characters:	PC347 □ Standard Europe □ Katakana □ PC850 □ Multilingual □ □ PC860 □ Portuguese □ □ PC863 □ Canadian- French □ □ PC865 □ Nordic □ West Europe □ Greek □ Hebrew □ East Europe □ Iran □ WPC1252 □ PC866 □ Cyrillic#2 □ □ PC852 □ Latin2 □ □ PC858 □ IranII □ Latvian □ Arabic □ PT151 □ 1251 □

