

## Handheld 1D/2D Barcode Reader (Model: OCBS-2004 )

### Specifications:

Performance Characteristics		
<b>Image Sensor:</b>		CMOS
<b>Resolution:</b>		752 * 480
<b>Light Source:</b>		LED(622 nm - 628 nm)
<b>Light Intensity:</b>		330 LUX (130 mm )
<b>Illumination:</b>		0 ~ 100,000 LUX
<b>Symbology:</b>	<b>2D</b>	PDF417, QR Code(Model 1/2), Data Matrix(ECC200, ECC000, 050, 080,100,140), Aztec, Maxicode, etc.
	<b>1D</b>	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar,etc.
<b>Precision:</b>		≥ 5mil
<b>Depth of Scan Field:</b>		35 mm ~ 210 mm
<b>Print Contrast Signal:</b>		≥ 30%
<b>Roll/ Pitch/ Skew:</b>		360°/±60°/±60°
Physical Characteristics		
<b>Interface:</b>		RS232 / USB
<b>Power Consumption:</b>		2 W
<b>Voltage:</b>		DC 5 V (4.5-5.5V)
<b>Current:</b>	Idle	78 mA (idle) 400 mA(working) 18 mA (standby)
<b>Weight:</b>		235 g
<b>Dimensions:</b>		156 * 68 * 83 mm
User Environment		
<b>Operate Temperature:</b>		-5degree C~+45degree C
<b>Storage Temperature:</b>		-40degree C~+60degree C
<b>Humidity:</b>		5% - 95%(non-condensing)
Safe		
<b>Certificates:</b>		FCC Part15 Class B, CE EMC Class B

### Product Details:



### Relevant documents:

Do you want to know more product information?Please Click here.

Specification  
User's Manual