

Latest Factory Kitchen 80mm Pos thermal receipt printer

(Model No.: OCPP-80X)



Features:

Supports multi 1D bar codes and 2D bar codes printing.

100M Ethernet port, ultra high speed data transmission.

Supports 256KB NV Logo storage and 2M big buffer memory.

Supports black mark detection and order reminding function,

USB+RS232+LAN three types of communication Ports

250mm/s high speed printing

Technical parameters

| | |
|---------------------|---|
| Printing method: | Direct thermal |
| Printing speed: | 250mm/s |
| Roll width: | 79.5±0.5mm |
| Print diameter: | Φ80mm |
| Paper thickness: | 0.06-0.08mm |
| Column capacity: | 576dots/line512 Dots/line |
| Line's pacing : | 3.75mmAdjustable by commands |
| Print command: | Compatible with the ESC/POS command |
| Interface type: | Serial+USB+Lan |
| Cutters life: | 1million cuts |
| Print head life: | 100 km |
| Input buffer : | 2048Kbytes |
| NV Flash: | 256Kbytes |
| Power adaptor: | AC110V/240V50~60Hz |
| Power supply: | DC 24V/2.5A |
| Cash drawer supply: | DC 24V/1A |
| Work environment: | Temperature(0~45) humidity(10~80%)Non- condense |

| | |
|--------------------------|--|
| Work environment: | Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense |
| Storage environment: | Temperature(-10~60°C); Humidity(10~90%) |
| Character size: | ANK FontA:1.5*3.0mm/ FontB 1.1*2.1mm |
| Barcode: | UPC-A/UPC-E/JA/EAN13/JAN8/EAN8/CODE39/ITF /CODE93/CODE128/QRCode/PDF417 (options) |
| Characters: | PC347 Standard Europe Katakana PC850 Multilingual PC860 Portuguese PC863 Canadian-French PC865 Nordic West Europe Greek Hebrew East Europe Iran WPC1252 PC866 Cyrillic#2 PC852 Latin2 PC858 IranII Latvian Arabic PT151 1251 |
| Physical characteristics | Weight: 1.45Kg; Appearance size: 190×145×143mm (length * width * height) |

Pics:





OCPP-80X





OCPP-80X





OCPP-80X





OCP-80X



Related Printers: </products/thermal-receipt-printer.htm> </products/thermal-receipt-printer.htm>