

# Manufacturer POS 2.4G Wireless Scanner for 1D Bar Code (Model: OCBS- W700 )

## PRODUCT FEATURES:

- Integrated non-volatile memory (can store about 500 barcodes);
- Outside communication distance can reach 100m, inside is 20m;
- 20 scanners can work in the same field without interfering each other;
- Plug and play;
- 800mA big capacity Li-battery.

## PRODUCT SPECIFICATIONS:

| PHYSICAL CHARACTERISTICS         |   |
|----------------------------------|---|
| Light Source:                    | Visible Red Laser 650 nm  |
| Scanner Dimensions:              | 160mm * 70mm * 40mm(W * H * D)  |
| Weight :                         | 300G  |
| Material:                        | ABS + PC  |
| Scanning Mode:                   | One line scanning; Manual / Automatic   |
| Indicator Way:                   | Buzzer and Indicator Light  |
| PERFORMANCE CHARACTERISTICS      |   |
| Width of Scan Field:             | 20mm@scanner window<br>260mm@260mm  |
| Depth of Scan Field:             | 4mil (0.1mm)/5-60mm<br>5mil (0.12mm)/10-100mm<br>10mil (0.25mm)/15-250mm<br>35mil (0.89mm)/140-600mm<br>43mil (1.1mm)/150-800mm |
| Scan Speed:                      | 120 scans/sec   |
| Scan Precision:                  | 0.10mm (pcs0.9)   |
| Printing Contrast:               | Minimum 30% reflection difference   |
| Error Rate:                      | 1/(6million)  |
| Decode Capability:               | International general 1D barcodes   |
| Current:                         | 60mA (working); $\leq 5\mu\text{A}$ (standby)   |
| Scanning Corner:                 | 32°   |
| Scanning Elevation:              | 68°   |
| Scanning Angle of Avertence:     | 52°   |
| Working Frequency:               | 2.4GHz  |
| Communication Distance:          | 100m (Open Places)<br>20m (Indoor)  |
| Communication Interface:         | USB   |
| USER ENVIRONMENT CHARACTERISTICS |   |
| Drop Specification:              | 2m free fall  |
| Laser Level:                     | Level-1 laser safety standard   |
| Charge Power:                    | DC5V  |

## Product Details:

