Manufacturer POS 2.4G Wireless Scanner for 1D Bar Code (Model: OCBS- W700)

PRODUCT FEATURES:

Integrated non-volatile memory (can store about 500 barcodes);

Outside communication distance can reach 100m, inside is 20m;

20 scanners can work in the same field without interfering each other;

Plug and play;

800mA big capacity Li-battery.

PRODUCT SPECIFICATIONS:

| PHYSICAL CHARACTERSTICS | |
|---------------------------------|---|
| Light Source: | Visible Red Laser 650 nm |
| Scanner Dimensions: | 160mm * 70mm * 40mm(W * H * D) |
| Weight : | 300G |
| Material: | ABS + PC |
| Scanning Mode: | One line scanning; Manual / Automatic |
| Indicator Way: | Buzzer and Indicator Light |
| PERFORMANCE CHARACTERSTICS | |
| Width of Scan Field: | 20mm@scanner window 260mm@260mm |
| Depth of Scan Field: | 4mil (0.1mm)/5-60mm 5mil (0.12mm)/10-100mm 10mil (0.25mm)/15-250mm 35mil (0.89mm)/140-600mm 43mil (1.1mm)/150-800mm |
| Scan Speed: | 120 scans/sec |
| Scan Precision: | 0.10mm (pcs0.9) |
| Printing Contrast: | Minimum 30% reflection difference |
| Error Rate: | 1/(6million) |
| Decode Capability: | International general 1D barcodes |
| Current: | 60mA (working); ≦5uA(standby) |
| Scanning Corner: | 32° |
| Scanning Elevation: | 68° |
| Scanning Angle of Avertence: | 52° |
| Working Frequency: | 2.4GHz |
| Communication Distance: | 100m (Open Places) 20m (Indoor) |
| Communication Interface: | USB |
| USER ENVIRONMENT CHARACTERSTICS | |
| Drop Specification: | 2m free fall |
| Laser Level: | Level-1 laser safety standard |
| Charge Power: | DC5V |

Product Details:

x x x x x x x x