

PORTABLE WIRELESS BARCODE SCANNER

(MODEL: OCBS-W700)

SPECIFICATIONS:

PHYSICAL CHARACTERISTICS	
Light Source:	Visible Red Laser 650 nm
Scanner Dimensions:	160mm * 70mm * 40mm(W * H * D)
Weight :	300G
Material:	ABS + PC
Scanning Mode:	One line scanning; Manual / Automatic
Indicator Way:	Buzzer and Indicator Light
PERFORMANCE CHARACTERISTICS	
Width of Scan Field:	20mm@scanner window 260mm@260mm
Depth of Scan Field:	4mil (0.1mm)/5-60mm 5mil (0.12mm)/10-100mm 10mil (0.25mm)/15-250mm 35mil (0.89mm)/140-600mm 43mil (1.1mm)/150-800mm
Scan Speed:	120 scans/sec
Scan Precision:	0.10mm (pcs0.9)
Printing Contrast:	Minimum 30% reflection difference
Error Rate:	1/(6million)
Decode Capability:	International general 1D barcodes
Current:	60mA (working); ≤5uA(standby)
Scanning Corner:	32°
Scanning Elevation:	68°
Scanning Angle of Avertence:	52°
Working Frequency:	2.4GHz
Communication Distance:	100m (Open Places) 20m (Indoor)
Communication Interface:	USB
USER ENVIRONMENT CHARACTERISTICS	
Drop Specification:	2m free fall
Laser Level:	Level-1 laser safety standard
Charge Power:	DC5V

Product Details:





Features

Simple but not easy

Integrated non-volatile memory (can store about 500 barcodes);



Outside communication distance can



reach 100m, inside is 20m;;

20 scanners can work in the same field
without interfering each other;



Plug and play;



800mA big capacity Li-battery.



III All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Red Laser 650 nm
Scanner Dimensions(W * H * D)	160mm * 70mm * 40mm
Weight	300G
Material	ABS + PC
Scanning Mode	One line scanning; Manual / Automatic
Indicator Way	Buzzer and Indicator Light
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	20mm@scanner window 260mm@260mm
Depth of Scan Field	4mil (0.1mm)/5-60mm 5mil (0.12mm)/10-100mm 10mil (0.25mm)/15-250mm 35mil (0.89mm)/140-600mm 43mil (1.1mm)/150-800mm

Scan Speed	120 scans/sec
Scan Precision	0.10mm (pcs0.9)
Printing Contrast	Minimum 30% reflection difference
Error Rate	1/(6million)
Decode Capability	International general 1D barcodes
Current	60mA (working); \leq 5uA(standby)
Scanning Corner	32°
Scanning Elevation	68°
Scanning Angle of Avertence	52°
Working Frequency	2.4GHz
Communication Distance	100m (Open Places) 20m (Indoor)
Communication Interface	USB
USER ENVIRONMENT CHARACTERSTICS	
Drop Specification	2m free fall
Laser Level	Level-1 laser safety standard
Charge Power	5VDC

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



0000000000 00 00 0000 000 00 00 00 0000 0000 0000 0000 0000 0000 0000 0000



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.



Relevant documents:

Do you want to know more product information? Please Click here.

[Specification](#)

[User Manual](#)