

Direct Thermal Label Printer

(M/N:OCBP-010)

Features:

1. With adjustable paper warehouse, it can be used in a variety of printing papers.
2. Thermal printing with no ribbon, no consumables, print by paper loading
3. Quickly position the paper with a dual media sensor to ensure accurate print position
4. Support up to 110mm width label paper, large width can be also easily printed
5. CPCL and TSPL programming language

Specification

Model	OCBP-010
Color	White
Interface	USB(Standard),USB+LAN,USB+BT,USB+LAN(Optional)
Printer Head life	50Km
Power supply	Input□AC 100V-240V,50-60Hz,Output□DC 24V/2.5A
Inner code	Support 11 types font size
Mechanical Noise	less than 60dB (A weighted RMS)
Compatible OS	Win9X/Win2000//Win2003/Win Vista/ Win 7/Window XP /win 8/win8.1/Win 10/IOS/Android
Safety standards	CE ,FCC,Rohs,CCC etc
Printing method	Direct Thermal
Resoluiton	8 dots/mm(203 DPI)
print speed	160 mm /s
Print width	104mm Max
Printing command	TSPL/ESC/POS
Barcode	1D barcode: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D barcode:QR Code, PDF417
Font	font A:12*24(standard), font B:9*17
Media	
Paper type	continuous paper, label paper, folded paper, tag paper
Paper width	110±0.5mm
Media thickness	0.06 ~ 0.3mm
Paper roll diameter	110mm Max
Physical	
Dimension	226mm*180mm *147 mm
Weight	Net: 1.65kg ,Gross: 1.95kg
Package box	300*200*165 mm
8 in 1 carton	600*400*350mm/16.65kg
Environment	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation













LABEL PRINTER

Application



Gross Weight: 2.0kg
Package Size: 232 x 130 x 162mm





